

# FEATURES AND BENEFITS

3 Rib front wheel design  
Easy steering



Strong nylon casing

Designed for  
two wheel  
drive tractors



Solid centre rib



## FARMAX F2

TRA CODE : IND-X

Size	Type	Rim inches	Outer Diameter	Section Width	Static Loaded radius	Rolling Circum - ference	PR	Inflation Pressure	Load Index / Speed Symbol	Load capacity (kg) (lbs)
			mm/in	mm/in	mm/in	mm/in		bar (psi)		
7.50-20	Tube Type	5.50F	914 36.0	205 8.1	428 16.9	2742 108.0	8	3.4 49	108 / A6	1030 2270
4.00-19	Tube Type	3.00D	712 28.0	112 4.4	333 13.1	2136 84.1	4	3.4 49	72 / A6	355 785
7.50-18	Tube Type	5.50F	860 33.9	205 8.1	402 15.8	2580 101.6	8	3.7 54	106 / A6	950 2095
7.50-16	Tube Type	5.50F	805 31.7	205 8.1	377 14.8	2415 95.1	8	3.7 54	103 / A6	875 1930
6.50-16	Tube Type	4.50E	760 29.9	175 6.9	356 14.0	2280 89.8	6	3.1 45	91 / A6	615 1355
6.00-16	Tube Type	4.50E	735 28.9	165 6.5	344 13.5	2205 86.8	6	3.4 49	88 / A6	560 1235
5.50-16	Tube Type	4.00E	710 28.0	150 5.9	332 13.1	2130 83.9	6	3.7 54	86 / A6	530 1170
11.00-16	Tube Type	W10	972 38.3	326 12.8	455 17.9	2916 114.8	8	2.5 36	118 / A6	1320 2910
10.00-16	Tube Type	W8	910 35.8	285 11.2	426 16.8	2730 107.5	8	2.8 41	115 / A6	1215 2680
5.00-15	Tube Type	4.00E	655 25.8	140 5.5	307 12.1	1965 77.4	4	2.8 41	73 / A6	365 805
10.00-16	Tube Type	W8	910 35.8	285 11.2	426 16.8	2730 107.5	12	3.4 49	119 / A6	1360 3000
11.00-16	Tube Type	W10	972 38.3	326 12.8	455 17.9	2916 114.8	12	2.5 36	118 / A6	1320 2910