

FEATURES AND BENEFITS

Robust deep lugs
Superior haulage
on all terrains



Advanced tyre compound
Extended tyre lifespan
Enhanced weather &
crack resistance

Dual-angle lug design
Optimal traction for
peak performance



Open buttress
design
Improved
self-cleaning



Tough nylon casing
Reliable stability,
puncture resistance

*Read more about warranty policy on page 89

FARMAX R1 HD



FARMAX R1 HD

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm/in	mm/in					Static	40
18.4-38	W16L	465	1750	819	5250	12 PR TT 154A8	2.9	7500	3750
		18.3	68.9	32.2	206.7		42	16530	8270

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm/in	mm/in					Static	40
23.1-26	DW20	587	1605	738	4670	12 PR TL 155A8	2.2	7750	3875
		23.1	63.2	29.1	183.9		32	17080	8540

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommended load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm/in	mm/in					Static	40
18.4-26	W16L	480	1470	693	4410	10 PR TT 144A8	2.3	5600	2800
		18.9	57.9	27.3	173.6		33	12340	6170