

FEATURES AND BENEFITS

Larger volume & footprint

Reduced compaction



Rounded shoulder

Reduced damage to crops



*Designed for on & off-road agricultural service

FLOTATION TX440

Size	Rim	Outer Diameter	Section Width	Static Loaded radius	Rolling Circumference	PR	Free rolling	Drive Wheel	Infl. Press.	Load Carrying Capacity, kg(lbs)							
							Load index	Load index		Free wheel				Drive wheel			
							Speed index	Speed index	bar psi	10	25	40	50	10	25	40	50
700/40-22.5	18 PR 173 A8	700	1170	510	3499	TL	24.00	6	10730	10080	8650	8190	7740	7300	6900	6500	5850
		27.6	46.1	20.1	137.8		DC	87	23630	22200	19050	18040	17050	16080	15200	14320	12890
700/40-22.5	24.00 DC	1170 46.1	700 27.6	512 20.2	3490 137.4	16	166A8, 162B	154A8, 150B	1.8	6590	5600	4710	4240	4660	3960	3330	3000
									26	14530	12345	10385	9350	10275	8730	7240	6615
									2.0	7010	5960	5010	4510	4970	4220	3550	3200
									29	15455	13140	11045	9945	10955	9305	7825	7055
									2.2	7420	6310	5300	4770	5250	4460	3750	3380
32	16360	13910	11685	10515	11575	9835	8265	7450									
600/50-22.5	18 PR 170A8	600	1205	540	3670	TL	20.00	6	9900	9300	7980	7560	7140	6720	6300	6000	5400
		23.6	47.4	21.2	144.4		DC	87	21810	20480	17580	16650	15730	14800	13880	13220	11890

Size	Rim	Outer Diameter	Section Width	Static Loaded radius	Rolling Circumference	PR	Free rolling Load index	Drive Wheel Load index	Infl. Press.	Load Carrying Capacity, kg(lbs)								
										Free wheel				Drive wheel				
										mm/in	mm/in	mm/in	mm/in	Speed index	Speed index	bar	psi	10
600/50-22.5	20.00 DC	1170 46.1	611 24.1	510 20.1	3472 136.7	16	165A8, 161B	153A8, 149B		2.2	6540	5560	4670	4200	4630	3940	3310	2980
										32	11415	12260	10295	9260	10205	8685	7295	6570
										2.4	6870	5840	4910	4420	4870	4140	3480	3130
										35	15145	12875	10825	9745	10735	9125	7670	6900
										2.6	7210	6130	5150	4640	5110	4340	3650	3290
										38	15895	13515	11355	10230	11265	9565	8045	7255
550/60-22.5	16.00 DC	1244 49.0	550 21.7	541 21.3	3597 141.6	16	166A8, 162B	154A8, 150B		2.4	6780	5770	4840	4360	4800	4080	3430	3090
										35	14945	12720	10670	9610	10580	8995	7560	6810
										2.6	7110	6040	5080	4570	5030	4270	3590	3230
										38	15675	13315	11200	10075	11090	9415	7915	7120
										2.8	7420	6310	5300	4770	5250	4460	3750	3380
										41	16360	13910	11685	10515	11575	9830	8265	7450
500/60-22.5	16.00 DC	1170 46.1	500 19.7	510 20.1	3385 133.3	16	163A8, 159B	151A8, 148B		2.8	6310	5370	4510	4060	4470	3800	3190	2870
										41	13910	11840	9945	8950	9855	8380	7030	6325
										3.0	6570	5580	4690	4220	4650	3950	3320	2990
										44	14485	12300	10340	9300	10250	8710	7320	6590
										3.2	6830	5800	4875	4390	4830	4110	3450	3110
										46	15060	12785	10750	9680	10650	9060	7605	6855