

FEATURES AND BENEFITS

Tough nylon casing,
Strong bead bundle

Improved performance
on slopes

Larger volume
& footprint
Reduced
compaction



Rounded
shoulder

Reduced damage
to crops

FLOTATION T422



FLOTATION T422

Size	Rim Width in	Unloaded dimension		Static Circum- ference	Rolling Circum- ference	PR	Infl. press	Load Carrying Capacity					Tread Depth	
		SW	OD					Load, Speed Symbol		Speed	Max Load	Max Load		mm
											(Free Rolling)	(Drive wheel)		
		mm/in	mm/in					mm/in	mm/in	Bar	Free Rolling	Drive wheel		kmph
				Psi			mph							
800/45-26.5	16.00 DC	31.5	52.9	23.0	158.1	16 PR	2.2	177 / 173	164 / 160	40	7300	5000	24	
							32	A8 / B	A8 / B	25	16094	11023	0.9	
		800	1343	585	4016	12 PR	1.7	170 / 167	158 / 155	40	6000	4250	24	
							25	A8 / B	A8 / B	25	13228	9370	0.9	
700/50-26.5	24.00 DC	27.6	52.5	23.0	156.9	16 PR	2.4	174 / 170	162 / 158	40	6700	4750	24	
							35	A8 / B	A8 / B	25	14771	10472	0.9	
		700	1333	585	3986	12 PR	1.8	169 / 165	157 / 154	40	5800	4125	24	
							26	A8 / B	A8 / B	25	12787	9094	0.9	
600/55-26.5	20.00 DC	23.6	52.5	23.0	156.9	16 PR	2.6	170 / 167	159 / 156	40	6000	4375	25	
							38	A8 / B	A8 / B	25	13228	9645	1.0	
		600	1333	585	3986	12 PR	2	165 / 161	153 / 149	40	5150	3650	25	
							29	A8 / B	A8 / B	25	11354	8047	1.0	
700/50-22.5	24.00 DC	27.6	49.0	21.7	146.1	16 PR	2.8	174 / 170	162 / 158	40	6700	4750	24	
							41	A8 / B	A8 / B	25	14771	10472	0.9	
		700	1245	550	3710	12 PR	2.2	168 / 164	156 / 153	40	5600	4000	24	
							32	A8 / B	A8 / B	25	12346	8818	0.9	
700/40-22.5	24.00 DC	27.6	46.1	20.1	138.7	16 PR	2.6	166 / 162	154 / 150	40	5300	3785	24	
							38	A8 / B	A8 / B	25	11684	8344	0.9	
		700	1170	510	3522	12 PR	2	160 / 157	148 / 144	40	4500	3150	24	
							29	A8 / B	A8 / B	25	9921	6945	0.9	
600/50-22.5	20.00 DC	23.6	46.1	20.1	137.7	16 PR	2.6	165 / 161	153 / 149	40	5150	3650	24	
							38	A8 / B	A8 / B	25	11354	8047	0.9	
		600	1170	510	3498	12 PR	2	159 / 156	147 / 144	40	4375	3075	24	
							29	A8 / B	A8 / B	25	9645	6779	0.9	
550/60-22.5	16.00 DC	21.7	48.7	21.3	146.5	16 PR	3	168 / 163	155 / 151	40	5600	3875	25	
							44	A8 / B	A8 / B	25	12346	8543	1.0	
		550	1238	540	3720	12 PR	2.3	160 / 156	148 / 144	40	4500	3150	25	
							33	A8 / B	A8 / B	25	9921	6945	1.0	
550/45-22.5	16.00 DC	21.7	42.1	18.5	126.2	16 PR	2.8	159 / 156	147 / 143	40	4375	3075	25	
							41	A8 / B	A8 / B	25	9645	6779	1.0	
		550	1070	470	3205	12 PR	2.1	153 / 149	141 / 137	40	3650	2575	25	
							30	A8 / B	A8 / B	25	8047	5677	1.0	
500/60-22.5	16.00 DC	19.7	46.1	20.1	133.1	16 PR	3.2	163 / 159	151 / 148	40	4875	3450	25	
							46	A8 / B	A8 / B	25	10748	7606	1.0	
		500	1170	510	3380	12 PR	2.4	157 / 154	145 / 142	40	4125	2900	25	
							35	A8 / B	A8 / B	25	9094	6393	1.0	