

FEATURES AND BENEFITS

Flat tread with large width

Self cleaning properties



Specially formulated tread compound

High ground contact area

for good traction on paved surface



Reinforced sidewall

Improved penetration resistance

PORT PRO SL

TRA CODE : IND-4 & 5

Size	PR	Type	Rim Width in	Flange Height in	Unloaded Dimension		Static Loaded Radius	Rolling Circum	Load Capacity					
					SW	OD			Infl. Prs.	25 kmph (15mph)	10 kmph (5mph)	5 kmph (3mph)	1 kmph (0.6mph)	Static
										Max Load	Max Load	Max Load	Max Load	Max Load
					mm/in	mm/in			mm/in	mm/in	bar	kg	kg	kg
psi	lbs	lbs	lbs	lbs	lbs									
18.00-33	40	TL	13.00	2.5	498	1877	862	5556	11.4	25000	27000	29000	32000	36000
					20	74	34	219	165	55000	59400	63800	70400	79200
18.00 - 25	40	TL	13.00	2.5	498	1673	768	4952	10	21250	22950	24650	27200	30600
					20	66	30	195	145	46845	50595	54345	59965	67460
18.00 - 25	40	TL	13.00	2.5	498	1673	768	4952	10.5	21250	22950	24650	27200	30600
					20	66	30	195	150	46845	50595	54345	59965	67460