

FEATURES AND BENEFITS



ROCK XL

TRA CODE : E3 / E4

Size	PR	Type	Rim Width in	Flange Height in	Unloaded Dimension		Static Loaded Radius	Rolling Circum	Load Capacity			
					SW	OD			Transport 50kmph/ (30mph)		Loading 10kmph/ (5 mph)	
									Max load	Infl. Prs.	Max load	Infl. Prs.
					mm/in	mm/in			kg	bar	kg	bar
		lbs	psi	lbs	psi							
16.00-25	32	TL	11.25	2	432	1493	682	4420	7300	6.5	12500	8.75
					17	59	27	174	16090	94	27560	127
16.00-25	40	TL	11.25	2	432	1493	682	4420	8200	8	14500	10
					17	59	27	174	18080	115	31970	145
21.00-25	40	TL	15	3	585	1759	800	5140	11850	6.25	20600	8.25
					23	69	31	202	26125	91	45415	120
18.00-25	40	TL	13.00	2.5	498	1673	764	4952	9750	7.0	17000	9.5
					20	66	30	195	21500	102	37480	138
18.00-33	40	TL	13.00	2.5	498	1877	866	5556	11200	7.0	19500	9.5
					20	74	34	219	24690	102	42990	138
21.00-35	36	TL	15.00	3.0	595	2052	953	6125	14000	6.25	24300	8.25
					23	81	38	241	30865	91	53570	120
24.00-35	48	TL	17.00	3.5	653	2175	998	6390	18500	6.5	31500	8.5
					26	86	39	252	40785	95	69445	125

Size	PR	Type	Rim Width in	Flange Height in	Unloaded Dimension		Static Loaded Radius	Rolling Circum	Load Capacity (on hard Improved Surface)		
					SW	OD			Load / Speed Index	Max Load	Infl. Prs.
										kg/lbs	
					mm/in	mm/in			mm/in	mm/in	kg
		lbs	psi								
12.00-24	20	TT	8.5	1.3	328	1257	590	3720	155 F	3875	7.9
					13	49	23	146		8540	115