

# FEATURES AND BENEFITS

Specially designed tread with heavy center mass  
Suitable for heavy duty service



Specially formulated compound  
Specially formulated compound

Extra deep tread with special compound

Resistance to cuts and chipping  
Higher durability



Extra deep thread  
Higher Durability



## TYROCK SUPER X3

TRA CODE : IND-X

Size	Rim inch	Outer Diameter	Section Width	Static Loaded radius	Rolling Circumference	Pr Load Index & Speed Symbol	Speed	Inflation Pressure	Load Capacity
		mm/inch	mm/inch	mm/inch	mm/inch		kmph	bar	Kg
							mph	PSI	lbs
440/80-24 (16.9-24)	W15Lx24	1310	438	590	3805	12PR	40	2.6	3250
		51.6	17.2	23.2	149.8	149 A8	25	38	7165
19.5L-24	W17L	1335	495	592	3880	12PR	40	230	3450
		52.6	19.5	23.3	152.8	151 A8	25	34	7600
18.4-24	W16Lx24	1375	475	612	4116	12PR	40	2.5	3875
		54.1	18.7	24.1	162	155 A8	25	36	8540
17.5L-24	W15Lx24	1252	445	560	3700	12PR	40	2.6	3000
		49.3	17.5	22	145.7	146 A8	25	38	6615
17.5L-24	W15Lx24	1252	445	560	3700	8PR	40	1.85	2430
		49.3	17.5	22	145.7	139 A8	25	27	5360
440/80-24 (16.9-24)	W15Lx24	1310	438	590	3805	8PR	40	2	2650
		51.6	17.2	23.2	149.8	142 A8	25	29	5840

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index Speed	Recommended load, kg (lbs)					
		SW	OD				Infl. Press.	Speed, km/h (mph)				
								Industrial Tractor				
		mm/in	mm/in				bar	Static	10	20	30	40
		psi	6	12	19	25						
43X16.00-20	W14Lx20	400	1100	470	3270	4 PR TL	1.4	3250	2060	1570	1400	1300
		15.7	43.3	18.5	128.7	133 A2	20	7160	4540	3460	3090	2870
15-19.5	11.75X19.5	382	1025	440	3040	6 PR TL	2.1	4420	2800	2130	1900	1760
		15.0	40.4	17.3	119.7	144 A2	30	9740	6170	4690	4190	3880
10.5/80-18	W9X18	280	910	400	2700	8 PR TL	2.8	3930	2060	1800	1720	1650
		11	35.8	15.7	106.3	125A8	41	8660	4540	3970	3790	3640
12.4-16	10LBX16	308	940	410	2790	4 PR TL	1.4	2260	1190	1040	990	950
		12.1	37.0	16.1	109.8	106A8	20	4980	2620	2290	2180	2090
27X8.5-15	7JA X145	218	693	310	2060	6 PR TL	3.1	1770	1120	850	760	710
		8.6	27.3	12.2	81.1	112 A2	45	3900	2470	1870	1680	1560
23X8.5-14	7JA X14	205	598	270	1780	4 PR TL	2.4	1060	670	510	460	420
		8.1	23.5	10.6	70.1	94A2	35	2340	1480	1120	1010	930

Size	Rim inch	Outer Diameter	Section Width	Static Loaded radius	Rolling Circumference	Pr Load Index & Speed Symbol	Speed	Inflation Pressure	Load Capacity
		mm/inch	mm/inch	mm/inch	mm/inch		kmph	bar	Kg
							mph	PSI	lbs
400/70-20	W13x20	1075	395	492	3228	16 PR	40	3.2	2800
		42.3	15.6	19.4	127.1	144 A8	25	46	6170
440/80-24 (16.9-24)	W15Lx24	1310	438	590	3805	8PR	40	2	2650
		51.6	17.2	23.2	149.8	142 A8	25	29	5840