

TREADS OF **EXCELLENCE** AWAIT YOU!

NEXT-GEN TYRES TO RULE ALL TERRAINS



INDEX

RADIAL

TORQUEMAX	1
FARMAX HPT	2
SPRAYMAX	3
SPRAYMAX PRO	4
FARMAX R65	5
FARMAX R65 X3	6
FARMAX R70/R75	7
FARMAX R80	8
FARMAX R85/R85 R2	9
FARMAX R90/R90 R2	10
MULTILOADMAX	11
YIELDMAX	12
YIELDMAX VFLEX	12
FARMAX RC	13
FLOATMAX FT	14
FLOATMAX RT	15
FLOATMAX CARGO XL	16
FLOATMAX VF X3	16
FARM IMPLEMENT 800R	17
FARM IMPLEMENT I - 1	17
HI-FLEX IMPLEMENT	18
LAWNMAX	18
LOAD PRO HARD SURFACE	19
LOAD PRO	19
LIFT PRO	20

BIAS

FARMAX R1	21
FARMAX R2	22
FARMAX F2	22
FARMAX X3 TF	23
FARMAX F2M	23
FARMAX R1 HD	24
YIELDMAX 23°	24
FARMAX AS	25
FARM IMPLEMENT AWI 305	25
FARM IMPLEMENT 404	26
FARM IMPLEMENT LP	26
HIGHWAY IMPLEMENT T422	27
FLOTATION PLUS	27

FLOTATION T422	28
T422 VALUE-PRO	28
FLOTATION TX440	29
TR 800	29
IRROGATOR	30
TURF XL	30
LOGGER XL	31
FOREST XL	31
GM LOADER HD	32
GRIP X HD	32
GRIP XL 5	33
GRIP XL HARD SURFACE	33
LOADER PRO HD	34
MPT 503	34
MPT 602	35
MPT 800	35
MPT 808	36
TYROCK	36
TYROCK SUPER	37
TYROCK SUPER X3	37
GRIPMASTER EX	38
GRADER XL	38
GRADER XL PLUS	39
GRIP MASTER - ND	39
LOADER XL	40
TRAC XL	40
C 305	41
ROCK XL	41
GRIP MASTER-XL	42
PORT PRO RX	42
PORT PRO TX	43
PORT XL PLUS	43
PORT PRO SL	44
PORT PRO SS	44
SLICK 404	45
SLICK 431	45
ELEVETA X3	46
ELEVETA PLUS	46
TRENCHER XL	47
LOAD INDEX & SPEED SYMBOL	48

TORQUEMAX

For High Power Tractors, Grain Carts & Air Seeders



Stepped lug design

Better grip



Tilted lug tip

Lower vibration at high speed



Wider tread width

Lower compaction



Stronger & wider lugs

Longer life



Lower lug angle at the shoulder

Better traction



Rounded shoulder

Lesser crop damage

SIZES

- VF520/80R26 CFO 168D TL SB
- VF620/70R26 173D TL SB
- VF750/65R26 180D TL SB CFO
- VF 520/60R28 149D TL SB
- VF540/65R28 154D TL SB
- VF600/60R28 157D TL SB
- VF600/65R28 163D TL SB
- VF600/70R30 70D TL
- VF540/65R30 NRO 158D TL SB
- VF600/60R30 NRO 162D TL SB
- VF600/70R30 170D TL SB
- VF620/75R30 172D TL SB
- VF620/70R30 175D TL SB
- VF710/55R30 165D TL SB
- VF710/60R30 171D TL SB
- VF710/65R30 CFO 179D TL SB
- VF800/65R32 184D TL SB
- VF900/60R32 193D TL SB
- VF380/85R34 149D TL SB
- VF420/85R34 159D TL SB
- VF580/80R34 178D TL SB
- VF600/60R34 160D TL SB NRO
- VF600/70R34 170D
- VF650/60R34 168D TL
- VF650/65R34 NRO 167D TL SB
- VF650/60R34 168D TL SB
- VF710/55R34 170D TL SB
- VF710/60R34 173D TL SB
- VF380/95R38 159D TL SB
- VF520/85R38 170D TL
- VF520/85R38 170D TL SB
- VF650/60R38 173D TL SB
- VF650/65R38 175D TL SB
- VF650/85R38 182D TL SB
- VF710/60R38 NRO 171D TL SB
- VF710/70R38 178D TL
- VF800/70R38 187D TL SB
- VF900/60R38 193D TL SB
- VF520/85R42 174D/177A8 TL
- VF520/85R42 174D/177A8 TL SB
- VF580/85R42 183D TL SB
- VF620/70R42 175D TL SB
- VF650/65R42 174D TL SB
- VF650/65R42 174D TL
- VF650/75R42 180D TL SB
- VF650/85R42 183D TL SB
- VF710/60R42 NRO 173D TL SB
- VF710/75R42 184D TL
- VF710/75R42 184D TL SB
- VF710/70R42 185D TL
- VF710/70R42 185D TL SB
- VF900/60R42 189D TL SB
- VF900/50R42
- VF750/70R44 186D TL SB
- VF380/85R46 162D TL SB
- VF520/85R46 179D TL SB
- VF620/70R46 179D TL SB
- VF750/75R46 189D TL SB
- VF900/65R46 196D TL SB
- IF520/85R38 167D TL
- IF600/70R30 165D TL
- IF900/75R32 185 TL SB
- IF600/70R34 167D TL
- IF650/60R34 159D TL
- IF600/70R34 160D TL
- IF710/70R38 178D TL
- IF710/70R38 181A8/178B FB TL
- IF800/70R38 CFO 190D TL SB
- IF710/75R42 176D TL
- IF710/75R42 176D TL SB
- IF710/70R42 179D TL
- IF850/75R42 186D TL SB

FARMAX HPT

For High Power Tractors



Stepped lug tip

Increases the grip and reducing the tractor slip



Extra wide tread

Higher footprint which gives better stability



Rounded shoulder

Provides less soil damage & better grip



Lug base tie bar

Additional support to lugs and also helps to remove mud from lugs



50° lug angle at centre

Smoother driving comfort, lesser noise and vibration



SIZES

- 600/65R28 154D TL
- 600/70R28 157D/160A8 TL
- 600/70R30 158D/161A8 TL
- 600/70R30 168D/171A8 TL
- 600/70R34 160D TL
- 650/65R34 161D TL
- 650/75R34 162D TL FB
- 650/75R38 169D TL
- 650/85R38 170D/173A8 TL
- 650/85R38 173D/176A8 TL
- 710/70R38 171D TL
- 710/70R38 178D/181A8 TL
- 800/70R38 178D TL
- 800/70R38 187D/190A8 TL SB
- 850/80R38 180D TL
- 710/70R42 173D TL
- 710/70R42 176D/179A8 TL
- 710/75R42 175D TL
- 710/75R42 181D TL
- 480/80R50 159D/162A8 TL
- 480/80R50 165D/168A8 TL
- 480/80R50 176D TL

SPRAYMAX

For Sprayers



Higher NSD

Longer life



Stepped lug design

Better grip & traction



Rounded shoulder

Prevents lesser soil and crop damage



Advanced VF technology

40% more load carrying capability than standard radial



SIZES

- VF 380/80R38 167D TL SB
- VF320/85R38 155D TL SB
- VF320/90R42 163D TL SB
- VF480/80R42 162D TL
- VF480/80R42 162D TL SB
- VF480/80R42 176D TL
- VF480/80R42 176D TL SB
- VF380/90R46 173D TL
- VF380/90R46 173D TL SB
- VF480/80R46 164D TL
- VF480/80R46 164D TL SB
- VF480/80R46 177D TL
- VF480/80R46 177D TL SB
- VF750/60R46 189D TL SB
- VF320/90R50 169D TL SB
- VF380/105R50 179D TL SB
- VF380/90R50 175D TL
- VF380/90R50 175D TL SB
- VF420/95R50 177D TL SB
- VF480/80R50 179D TL
- VF480/80R50 179D TL SB
- VF480/95R50 181D TL SB
- VF320/90R54 168D TL SB
- VF380/105R54 168D TL SB
- VF380/105R54 180D TL SB
- VF380/90R54 176D TL
- VF480/95R54 180D TL SB
- VF380/90R54 176D TL SB
- VF380/90R46 173D TL SB CFO

SPRAYMAX PRO

Self Propelled Sprayers



Optimised void ratio

Improved roadability and smoother transport performance



Precisely angled lugs

Superior traction with reduced vibration on road



Reinforced radial casing and rigid belt

High load carrying capacity with enhanced durability



All weather performance design

Reliable performance across diverse terrains and conditions



SIZES

- VF380/90R46 CFO 175D

FARMAX R65

For Low To Mid HP Tractors



Tilted lug tip

Lesser vibration & noise



Mud breaker

Better self cleaning



Higher angle & lug overlap at centre

Better roadability



Wider tread larger inner volume

Reduces soil compaction



R1-W tread depth

Longer tyre life



Lower angle at shoulder

Superior traction



Rounded shoulder

Lesser damage to soil & crop

SIZES

- 320/65R16 117D TL
- 320/65R18 109D TL
- 340/65R18 122D TL
- 340/65R20 124D TL
- 420/65R20 135D TL
- 440/65R20 138D TL
- 420/65R24 138D TL
- 440/65R24 128D TL
- 440/65R24 135D TL
- 480/65R24 133D TL
- 480/65R24 140D/143A8 TL
- 540/65R24 140D TL
- 540/65R24 146D TL
- 540/65R26 141D TL
- 440/65R28 138D TL
- 600/65R28 147D/150A8 TL
- 600/65R28 154D TL
- 600/65R30 149D TL
- 600/65R30 155D TL
- 540/65R34 145D TL
- 540/65R34 152D TL
- 600/65R34 151D TL
- 600/65R34 157D TL
- 540/65R38 147D TL
- 540/65R38 153D TL
- 600/65R38 153D TL

FARMAX R65 X3

For Low To Mid HP Tractors



Directional & robust lugs

Provides higher traction



Robust centre blocks

Low noise & smooth rides



Rounded shoulders

Lesser soil damage



Through grooves

Better self-cleaning



SIZES

- 540/65R24 146D TL FB
- 480/65R28 142D TL FB
- 540/65R28 149D TL
- 540/65R30 150D TL
- 540/65R34 152D TL FB
- 650/65R38 163D TL
- 650/65R42 170D TL

FARMAX R70/ R75

For Low To Mid HP Tractors



Tilted lug tip

Lesser vibration & noise



Mud breaker

Better self cleaning



Higher angle & lug overlap at centre

Better roadability



Wider tread larger inner volume

Reduces soil compaction



R1-W tread depth

Longer tyre life



Lower angle at shoulder

Superior traction



Rounded shoulder

Lesser damage to soil & crop

SIZES

- 200/70R16 94D/97A8 TL
- 240/70R16 104D/107A8 TL
- 260/70R16 109D/112A8 TL
- 280/70R16 112D/115A8 TL
- 280/70R18 114D/117A8 TL
- 260/70R20 TL 113D/115A8
- 280/70R20 TL 116D/119A8
- 300/70R20 TL 110D/113A8
- 300/70R20 TL 120D/123A8
- 320/70R20 TL 113D/116A8
- 320/70R20 TL 123D/126A8
- 360/70R20 TL 120D/123A8
- 360/70R20 TL 129D/132A8
- 380/70R20 TL 122D/125A8
- 380/70R20 TL 132D/135A8
- 320/70R24 TL 116D/119A8
- 360/70R24 TL 122D/125A8
- 380/70R24 125D TL
- 420/70R24 130D TL
- 480/70R24 TL 138D/141A8
- 320/70R28 TL 119D/122A8
- 360/70R28 TL 125D/128A8
- 380/70R28 TL 127D/130A8
- 420/70R28 133D TL
- 480/70R28 TL 140D/143A8
- 480/70R28 TL 151D/154A8
- 600/70R28 161D/164A8 TL
- 420/70R30 TL 134D/137A8
- 480/70R30 147D/150A8 TL
- 480/70R30 TL 141D/144A8
- 520/70R30 TL 145D/148A8
- 600/70R30 158D TL
- 600/70R30 TL 152D/155A8
- 480/70R34 155D/158A8 TL
- 480/70R34 TL 143D/146A8
- 480/70R34 TL 149D/152A8
- 520/70R34 168D/171A8 TL
- 520/70R34 TL 148D/151A8
- 480/70R38 TL 145D/148A8
- 520/70R38 150D TL
- 580/70R38 170D/173A8 TL
- 580/70R38 180D/183A8 TL
- 580/70R38 TL 155D/158A8
- 710/70R38 178D TL
- 710/70R38 TL 172D/175A8
- 580/70R42 158D/161A8 TL
- 620/70R42 166D/169A8 TL
- 620/70R42 173D/176A8 TL
- 710/70R42 173D TL
- 400/75R38 138D/141A8 TL

FARMAX R80

For Low To Mid HP Tractors



R1-W tread depth

Longer tyre life



Higher angle and lug overlap at centre

Better roadability



Wider tread larger inner volume

Reduces soil compaction



Rounded shoulder

Lesser damage to soil and crop



Lower angle at shoulder

Superior traction



SIZES

- 480/80R26 143D/146A8 TL
- 380/80R38 142A8/B TL
- 380/80R38 152A8/B TL
- 380/80R38 154D/157A8 TL
- 480/80R42 151D/154A8 TL
- 480/80R42 153D/156A8 TL
- 480/80R42 169D/172A8 TL
- 420/80R46 151D/154A8 TL
- 420/80R46 159D/162A8 TL
- 480/80R46 158D/161A8 TL
- 480/80R46 164D/167A8 TL
- 480/80R38 149D TL FB

FARMAX R85/R85 R2

For Low To Mid HP Tractors



R1-W tread depth

Longer tyre life



Higher angle and lug overlap at centre

Better roadability



Wider tread larger inner volume

Reduces soil compaction



Rounded shoulder

Lesser damage to soil and crop



Lower angle at shoulder

Superior traction

SIZES

- 180/85R12 80A8/B TL
- 250/85R20 TL 116D/119A8
- 280/85R20 TL 112D/115A8
- 320/85R20 TL 119D/122A8
- 250/85R24 TL 109D/112A8
- 280/85R24 TL 115D/118A8
- 320/85R24 TL 122D/125A8
- 320/85R24 TL 142D/145A8
- 340/85R24 125D TL
- 380/85R24 131D TL
- 420/85R24 TL 137D/140A8
- 420/85R26 (16.9R26) 138D/141A8 TL
- 250/8528 TL 112D/115A8
- 280/85R28 TL 118D/121A8
- 320/85R28 TL 124D/127A8
- 340/85R28 TL 127D/130A8
- 380/85R28 133D TL
- 420/85R28 TL 139D/142A8
- 380/85R30 TL 135D/138A8
- 420/85R30 140D TL
- 420/85R30 TL 147D/150A8
- 460/85R30 TL 145D/148A8
- 320/85R32 145D/148A8 TL
- 320/85R32 TL 126D/129A8
- 320/85R32 TL 142D/145A8
- 320/85R34 TL 141D/144A8
- 380/85R34 TL 137D/140A8
- 420/85R34 142D TL
- 420/85R34 TL 147D/150A8
- 460/85R34 TL 147D/150A8
- 460/85R34 TL 157D/160A8
- 320/85R36 TL 128D/131A8
- 340/85R36 TL 132D/135A8
- 320/85R38 143D/146A8 TL
- 340/85R38 151D/154A8 TL
- 340/85R38 TL 133D/136A8
- 340/85R38 TL 148D/151A8
- 420/85R38 TL 144D/147A8
- 460/85R38 153D/156A8 TL
- 460/85R38 TL 149D/152A8
- 460/85R38 TL 167D/170A8
- 520/85 R38 TL 169D/172A8
- 520/85R38 TL 155D/158A8
- 520/85R42 169D/172A8 TL
- 520/85R42 TL 157D/160A8
- 520/85R46 TL 174D/177A8
- 520/85R46 TL 158D/161A8
- 380/85R26 132D/135A8 TL FB
- 460/85R26(18.4R26) 143D TL
- 460/85R42 156D/159A8 TL FB
- 520/85R42 R2 157A8/B TL
- 520/85R50(20.8R50) 165D/168A8

FARMAX R90

For Low To Mid HP Tractors



R1-W tread depth

Longer tyre life



Higher angle and lug overlap at centre

Better roadability



Wider tread larger inner volume

Reduces soil compaction



Rounded shoulder

Lesser damage to soil and crop



Lower angle at shoulder

Superior traction

SIZES

▪ 420/90R30 142D/145A8 TL

▪ 420/90R30 147D/150A8 TL

FARMAX R90 R2

For Low To Mid HP Tractors



Extra-deep tread, with curved tread bars

Better self cleaning & traction in wet soil



Flatter tread

Reduces soil compaction



Dual step tie bar

Prevents mud clogging while adding traction & side hill slip resistance



Stepped lug design

Good grip in wet & moist soil



Buttressed bar base

Better self cleaning

SIZES

▪ 420/90R30 147A8/B TL

MULTILOADMAX

For Multipurpose Application



Big centre block

Gives better stability on road



Unique angular grooves

Better driving comfort & self cleaning



Steel belted carcass

Uniform load distribution and good puncture & impact resistance



Robust block design

Good traction on-road & off-road



SIZES

- 250/80R16 123D/127A8 TL
- 265/70R16.5 130A2 TL SB
- 305/70R16.5 141A5 TL SB
- 340/80R18 138D/143A8 TL SB
- 400/70R18 143D/147A8 TL SB
- 360/70R20 131D/136A8 TL SB
- 360/80R20 143D/147A8 TL SB
- 400/70R20 144D/149A8 TL SB
- 360/80R24 145D/150A8 TL SB
- 400/80R24 151D/156A8 TL SB
- 440/80R24 156D/161A8 TL SB
- 500/70R24 159D/164A8 TL SB
- 540/70R24 170D/175A8 TL SB
- 360/80R28 142D/146A8 TL SB
- 400/80R28 153D/158A8 TL SB
- 440/80R28 158D/163A8 TL SB
- 440/80R30 153D/157A8 TL SB
- 600/70R30 166D/171A8 TL SB
- 440/80R34 155D/159A8 TL SB
- 480/80R34 159D/164A8 TL SB
- 480/80R38 161D/166A8 TL SB
- 540/80R38 167D/172A8 TL SB
- 710/70R42 180D/185A8 TL SB
- 360/70R17.5 156A2 TL SB

YIELDMAX

For Combine Harvesters



R1-W pattern

Longer tyre life



Dual lug angle

Higher traction and better stability



Higher lug overlap

Enhances roadability and loadability



Strong and sharp shoulders

Better grip



SIZES

- 620/75R26 CHO 166A8/B TL
- 620/75R26 CHO 166 A8/B TL SB
- 750/65R26(28LR26) 173A8/170B TL
- 620/75R30 CHO 169A8/B TL SB
- 1050/50R32 184A8/B TL SB
- 650/75R32 CHO 172A8/B TL
- 650/75R32 CHO 172A8/B TL SB
- 800/65R32 CHO 181A8/B TL
- 800/65R32 CHO 181A8/B TL SB
- 800/70R32 181A8 TL SB
- 900/60R32 193A8/B TL SB
- 620/75R34 CHO 170A8/B TL SB
- 710/75R34 178A8/178B TL

YIELDMAX VFLEX

For Combine Harvesters



Directional tread pattern

Comfortable ride and reduced wear rate



Ultra-wide tire design

Large contact area and reduced soil damage



Large center block

Enhances traction performance



SIZES

- VF750/50R26 174D TL SB
- VF1000/55R32 197D TL SB
- VF680/85R32 184D TL SB
- IF1250/50R32 201D TL SB
- VF1000/50R25 190D TL SB

FARMAX RC

For Row Crop



Higher angle and lug overlap at center

Better roadability and stability



Rounded shoulder

Reduces damage to soil and crops



Higher number of lugs

Superior traction



Strong carcass and bead

Higher load carrying capacity



SIZES

- 210/95R32 117D/120A8 TL
- 230/95R32 128D/131A8 TL
- 270/80R32 131D/134A8 TL
- 270/95R32 133D/136A8 TL
- 210/95R36 118D/121A8 TL
- 230/95R36 127D/130A8 TL
- 230/95R36 130D/133A8 TL
- 270/95R36 136D/139A8/B TL
- 270/95R38 137D/140 A8 TL
- 270/95R38 140D/143A8 TL
- 230/95R40 132D/135A8 TL
- 230/95R42 133D/136A8 TL
- 270/95R42 137D/140A8 TL
- 270/95R42 139D/142A8 TL
- 300/95R42 147D/150A8 TL
- 320/80R42 141D/144A8 TL
- 320/90R42 136D/139A8 TL
- 320/90R42 144D/147A8 TL
- 210/95R44 120D/123A8 TL
- 230/95R44 129D/132A8 TL
- 230/95R44 134D/137A8 TL
- 270/95R44 140D/143A8 TL
- 270/95R44 142D/145A8 TL
- 270/95R46 141D/144 A8 TL
- 300/95R46 143D/146A8 TL
- 300/95R46 148D/151A8 TL
- 320/90R46 146D/149A8 TL
- 320/90R46 148D/151A8 TL
- 340/85R46 147D/150A8 TL
- 340/85R46 150D/153A8 TL
- 380/90R46 159D/162A8 TL
- 380/90R46 162D/165A8 TL
- 380/90R46 165A8/B TL
- 230/95R48 136D/139A8 TL
- 270/95R48 142D/145A8 TL
- 340/85R48 148D/151A8 TL
- 340/85R48 156D/159A8 TL
- 320/90R50 150D/153A8 TL
- 380/105R50 168D/171A8 TL
- 380/90R50 151D/154A8 TL
- 380/90R50 158D/161A8 TL
- 300/95R52 149D/152A8 TL
- 300/95R52 151D/154A8 TL
- 270/95R54 149D/152A8 TL
- 270/95R54 146D/149A8 TL
- 320/90R54 153D/156A8 TL

FLOATMAX FT

For Tankers & Trailers



Directional lug

Superior traction



Robust centre blocks

Better stability & roadability



Wider & flatter crown

Better floating characteristics



Rounded shoulder

Lesser damage to soil & crop



SIZES

- 440/55R18 159A8/B TL SB
- 560/45R22.5 152D TL
- 560/45R22.5 152D TL SB
- 500/60R22.5 155D TL
- 500/60R22.5 155D TL SB
- 500/60R22.5 163D TL SB
- 600/50R22.5 159D TL
- 600/50R22.5 159D TL SB
- 600/50R22.5 168B TL SB
- 560/60R22.5 161D TL
- 560/60R22.5 164D TL SB
- 710/40R22.5 161D TL SB
- 650/50R22.5 163D TL SB
- 580/65R22.5 166D TL SB
- 710/45R22.5 165D TL SB
- 600/55R26.5 165D TL
- 800/40R22.5 170D TL SB
- 800/40R22.5 176B TL SB
- 600/55R26.5 165D TL SB
- 650/55R26.5 178D TL SB
- 650/60R26.5 173D TL SB
- 750/45R26.5 170D TL SB
- 600/55R26.5 178D TL SB
- 650/65R26.5 174D TL SB
- 710/50R26.5 170D TL SB
- 850/40R26.5 173D TL SB
- 800/45R26.5 174D TL SB
- 710/50R30.5 173D TL
- 650/65R30.5 176D TL SB
- 750/60R30.5 181D TL SB
- 850/50R30.5 182D TL SB
- 800/60R32 185D TL SB

Floatmax RT

For Spreaders, Tankers & Trailers



Directional lug

Higher traction, comfortable ride



Robust centre blocks

Low noise and smooth run on hard surface



Flatter crown width

Larger footprint, lower Soil compaction



Rounded shoulder

Lesser damage to soil and crops



Interconnected grooves

Better self-cleaning properties

SIZES

- 385/65R22.5 164D TL SB
- 500/60R22.5 155D TL SB
- 560/45R22.5 152D TL SB
- 560/60R22.5 165D TL SB
- 560/60R22.5 169D TL SB
- 580/65R22.5 166D TL SB
- 650/50R22.5 163D TL SB
- 600/55R26.5 165D TL SB
- 600/55R26.5 178D TL SB
- 650/55R26.5 178D TL SB
- 710/50R26.5 172D TL SB
- 710/50R26.5 181D TL SB
- 600/60R30.5 173D TL SB
- 650/65R30.5 176D TL SB
- 710/50R30.5 173D TL SB
- 750/60R30.5 181D TL SB
- 850/50R30.5 182D TL SB
- 500/60R22.5 163DTL SB

FLOATMAX CARGO XL

For Spreaders, Tankers & Trailers



Non-directional and robust lugs

High traction



Robust center blocks

Reduces noise & Improves comfort on hard surfaces



Rounded shoulder

Reduces crop damage



Flat crown width

Larger footprint for improved floatation



SIZES

- 28LR26(750/65R26) 176D TL SB
- 620/75R26 174D TL SB
- 800/60R32 185D TL SB
- VF900/65R32 197D TL SB
- VF850/50R30.5 188D TLSB

FLOATMAX VF X3

For Tankers, Trailers & Agri-trucks



Distinctive tread pattern

Superior handling and self-cleaning



Robust center block

Improves stability



Steel-belted carcass

Enhances impact protection



VF Casing

Reduces soil compaction



SIZES

- VF500/50R17
- VF560/60R22.5 TL SB
- VF710/45R22.5 170D TL SB
- VF600/55R26.5 170D TL SB
- VF650/60R26.5 174D TL SB
- VF650/65R26.5 179D TL SB
- VF750/60R30.5 187D TL SB

FARM IMPLEMENT 800R

For Implements



Rib pattern

Wider footprint & lower ground pressure



Lugs with rounded shoulders

Excellent self-cleaning capabilities



Special shoulder design

Strong grip



Steel belted construction

Protection from punctures



SIZES

- 340/60R16.5 145A8 TL SB
- 380/55R16.5 150A8/B TL SB
- 500/40R16.5 153A8 TL SB
- 500/50R17 151D TL SB
- 440/55R18 159A8/B TL SB
- 500/45R20 157A8 TL SB
- 620/40R22.5 154D TL SB
- 620/50R22.5 161D TL SB
- VF445/50R22.5 167D TL SB
- 620/55R26.5 166D TL SB

FARM IMPLEMENT I-1

For Implements



Flotation Ribs

Ribs enhance flotation, enabling easier steering and improved equipment stability



High Rubber Volume

Greater rubber volume reduces wear and extends overall tire life



Rounded Shoulders

Rounded shoulders make the tire ideal for seeders and agricultural implements



SIZES

- 200/60-14.5 14PR TL
- 250/65-14.5 14PR TL

HI-FLEX IMPLEMENT

For Bailers, Seeders & Grain Carts



Reinforced sidewall & bead

Longer tyre life



Rounded Shoulder

Lesser damage to soil and crops



Steel belt at crown

Puncture resistance



IF Construction

Carries heavier load at low inflation pressure



SIZES

- IF240/80R15 125D TL
- IF265/85R15 129D TL SB
- IF280/70R15 137D TL SB
- IF320/70R15 146D TL SB
- VF270/65R16 135D TL SB
- VF340/65R18 149D
- VF270/65R18 137D TL SB

LAWNMAX

For Lawn & Turf



Higher tread depth

Provides superior traction and longer life



Rounded shoulder design

Helps with low soil compaction



Lawnmax tread design

Better self-cleaning



Directional tread pattern

Minimises wear



SIZES

- 220/55R12 82A8/B TL
- 240/60R12 89A8/B TL
- 215/65R14 90A8/B TL
- 200/60R15 83A8/B TL
- 200/65R16 94A8/B TL
- 200/70R16 94A8/B TL FB
- 240/70R16 104A8/B TL
- 260/70R16 109A8/B TL
- 280/70R16 112A8/B TL
- 260/70R18 114A8/B TL FB
- 280/70R18 114A8/B TL
- 320/65R18 109A8/B TL
- 300/70R20 110A8/B TL
- 320/70R20 113A8/B TL
- 380/70R20 122A8/B TL
- 360/70R24 122A8/B TL
- 380/70R24 125A8/B TL
- 420/70R24 130A8/B TL
- 320/85R28 124A8/B TL FB
- 340/85R28 127A8/B TL
- 480/70R30 141A8/B TL FB

LOADPRO HARD SURFACE

For Telehandlers



Non-directional

Provides better traction and Stronger grip



Center of tie bar

Outstanding comfort



Higher base width

Better roadability and Higher traction



SIZES

- 405/70R18 147A8 SBTL
- 405/70R20 149A8/B TL SB
- 460/70R24 159 A8/B TL SB
- 500/70R24 164A8/B TL SB
- 340/80R18 143A8 SBTL
- 440/80R24 161A8 TLSB
- 405/70R24 152A8 TLSB
- 365/70R18 142A8 TLSB
- 400/80R24 162A8 TLSB

LOADPRO

For Telehandlers



Greater lug overlap and more lugs in footprint

Uniform load distribution



Extra reinforced sidewalls

Additional lateral stability



Strong bead

Better carcass strength and load carrying capacity



SIZES

- 400/80-24 162A8 TL
- 440/80-24 168A8 TL
- 440/80-28(16.9-28) 156A8 TL
- 280/80R18 R-4 132A8/B TL SB
- 300/75R18 R-4 142A8/B TL SB
- 340/80R18 R-4 143A8/B TL SB
- 280/80R20 R-4 133A8/B TL SB
- 380/75R20 R-4 148A8/B TL SB
- 400/70R20(16.0/70R20) R-4 149A8/B TL SB
- 405/70R24 R-4 152A8/B TL SB
- 440/80R24 R-4 161A8/B TL SB
- 460/70R24(17.5LR24) R-4 159 A8/B TL SB
- 500/70R24 (19.5LR24) R-4 164A8/B TL SB
- 480/80R26(18.4R26) R-4 160A8/B TL SB
- 480/80R26(18.4R26) R-4 167A8/B TL SB
- 440/80R28(16.9R28) R-4 156A8/B TL SB
- 500/70R28 R-4 164A8/B TL SB

LIFTPRO

For Telehandlers & Boom Lifters



Unique R1 pattern

Excellent traction



Deep under tread

Improves puncture resistance



Strong nylon casing & thick sidewall

High radial & lateral stability



SIZES

▪ 15.5/80-24 16PR TL

▪ 460/70R24 159A8/B TL

FARMAX R1

For Harvester & Tractor



Triple angle lug

Enhances traction & roadability



High centre lug overlap & tie bar

Improves stability



SIZES

- 7.00-12 10PR TL
- 7.00-12 6PR TL
- 12.4-16 6PR TL
- 6.50-16 6PR TT
- 7.50-16 6PR TT
- 7.50-16 8PR TT
- 8.25-16 6PR TT
- 8-16 8PR TL
- 9.5-16 12PR TL
- 9.5-16 8PR TL
- 250/80-18 8PR TT
- 7.50-20 8PR TT
- 8.00-20 8PR TT
- 9.5-20 8PR TT
- 9.5-22 8PR TT
- 11.2-24 10PR TT
- 11.2-24 8PR TL
- 11.2-24 8PR TT
- 11.2-28 8PR TL
- 12.4-24 10PR TT
- 12.4-24 12PR TT
- 12.4-24 8PR TT
- 12.4-24 8PR TL
- 12.4-28 8PR TL
- 12.4-28 8PR TT
- 13.6-28 12PR TL
- 13.6-28 8PR TT
- 14.9-28 12PR TL
- 14.9-28 12PR TT
- 14.9-28 8PR TT
- 14.9-28 8PR TL
- 16.9-28 12PR TL
- 16.9-28 12PR TT
- 16.9-28 8PR TT
- 14.9-30 8PR TL
- 14.9-30 8PR TT
- 16.9-30 10PR TT
- 16.9-30 12PR TL
- 16.9-30 12PR TT
- 16.9-30 6PR TL
- 16.9-30 8PR TT
- 11.2-28 8PR TT
- 11.2-28 10PR TL
- 12.4-28 4PR TL
- 12.4-28 8PR TL
- 12.4-28 8PR TT
- 13.6-28 12PR TL
- 13.6-28 8PR TT
- 14.9-28 12PR TL
- 14.9-28 12PR TT
- 14.9-28 8PR TT
- 14.9-28 8PR TL
- 16.9-28 12PR TL
- 16.9-28 12PR TT
- 16.9-28 8PR TT
- 14.9-30 8PR TL
- 14.9-30 8PR TT
- 16.9-30 10PR TT
- 16.9-30 12PR TL
- 16.9-30 12PR TT
- 16.9-30 6PR TL
- 16.9-30 8PR TT
- 18.4-30 12PR TT
- 18.4-30 14PR TT
- 18.4-30 14PR TL
- 18.4-30 8PR TL
- 18.4-30 8PR TT
- 23.1-30 12PR TL
- 12.4-32 8PR TT
- 24.5-32 12PR TL
- 16.9-34 10PR TT
- 16.9-34 14PR TT
- 16.9-34 8PR TL
- 16.9-34 8PR TT
- 18.4-34 10PR TT
- 18.4-34 12PR TT
- 18.4-34 14PR TL
- 18.4-34 14PR TT
- 18.4-34 8PR TT
- 12.4-36 12PR TT
- 12.4-36 8PR TL
- 12.4-36 8PR TT
- 13.6-36 8PR TL
- 13.6-36 8PR TT
- 12.4-38 14PR TT
- 12.4-38 8PR TT
- 13.6-38 14PR TT
- 13.6-38 8PR TT
- 13.6-38 10PR TL
- 13.6-38 8PR TL
- 15.5-38 10PR TT
- 15.5-38 12PR TT
- 15.5-38 8PR TT
- 15.5-38 8PR TL
- 16.9-38 10PR TT
- 16.9-38 12PR TL
- 16.9-38 12PR TT
- 16.9-38 8PR TT
- 18.4-38 12PR TT
- 18.4-38 8PR TT
- 18.4-38 8PR TL
- 20.8-38 10PR TT
- 20.8-38 10PR TL
- 20.8-38 14PR TL
- 12.4-24 10PR TL
- 18.4-30 12PR TL

DUAL BEAD

FARMAX R2

For Tractors used in Rice & Sugarcane Farming



Extra-deep tread with curved tread bars

Better self cleaning & traction in wet soil



Tie bar at the center

Strengthened lug base for better stability



Stepped lug design

Adds grip in wet & moist soil



Buttressed bar base

Better self cleaning



Bolstered nose at tread center

Improves wear and performance



SIZES

- 18.4-38 12PR TL
- 14.9-24 6PR TT
- 14.9-24 8PR TT

- 18.4-26 10PR TT
- 23.1-26 10PR TT
- 14.9-28 10PR TT

- 14.9-28 8PR TT
- 23.1-30 10PR TT
- 20.8-38 10PR TT

FARMAX F2

For Implements & Tractors



3 Rib front wheel design

Easy steering



Strong nylon casing

Designed for two wheel drive tractors



SIZES

- 5.00-15 4PR TT
- 10.00-16 8PR TT
- 11.00-16 8PR TT

- 5.50-16 6PR TT
- 6.00-16 6PR TT
- 6.50-16 6PR TT

- 7.50-16 8PR TT
- 7.50-18 8PR TT
- 4.00-19 4PR TT

- 7.50-20 8PR TT
- 7.50-16 12PR TT

FARMAX X3 TF

For Implements & Tractors



Unique tread design with grooves on the central rib and notches in the shoulder

Superior traction



Angular & open shoulder blocks

Better self-cleaning & longer life



4-Rib pattern

Driving comfort on and off road



Superior tread compound

Resistance to chips and tears
Excellent steering ability



SIZES

- 5.50-16 6PR TT
- 6.50-16 8PR
- 6.50-20 8PR TT
- 6.00-16 6PR TT
- 7.50-16 8PR TT
- 7.50-20 8PR TF

FARMAX F2M

For Implements



Multi rib design

Easy steering



Cut-resistant compound

Improves tyre life



SIZES

- 10.00-16 10PR TL
- 10.00-16 8PR TT
- 11.00-16 8PR TL
- 10.00-16 8PR TL
- 11.00-16 12PR TL
- 11.00-16 8PR TT

FARMAX R1 HD

For Harvesters



Robust deep lugs

Superior haulage on all terrains



Dual-angle lug design

Optimal traction for peak performance



Open buttress design

Improves self-cleaning



Tough nylon casing

Reliable stability, puncture resistance



SIZES

▪ 18.4-26 10PR TT

▪ 23.1-26 12PR TL

▪ 18.4-38 12PR TT

YIELDMAX 23°

For Harvesters



Stepped sidewall design

Improves performance on slopes



Tie bar at the center

Strengthened lug base for better stability



23° tread Bars

Best for traction



Buttressed bar base

Better self-cleaning



Stronger carcass

Carries heavier loads



SIZES

▪ 28L-26 12PR TL

▪ 24.5-32 12PR TL

▪ 24.5-32 14PR TL

▪ 30.5L-32 14PR TL

▪ 30.5L-32 18PR TL DUAL BEAD

FARMAX AS

For Implements & Agri Utility Tractors



Robust lug design

High traction and long life



Superior tread compound

Resistance to chips and tears



Reinforced carcass

Better loadability & longer life



SIZES

- 5.00-10 8PR TT
- 23X10.50-12 12PR TL

- 6.5/80-12 6PR R1 TT
- 10.0/75-15.3 10PR TL

- 10.0/75-15.3 14PR TL
- 11.5/80-15.3 12PR TL

FARM IMPLEMENT AWI 305

For Implements



Non directional tread pattern

Prevents skidding while turning



Lugs are open & angled at the shoulder

Ensures maximum stability



Larger footprint

Designs for agricultural use



SIZES

- 10.0/80-12 10PR TL
- 10.0/80-12 8PR TL
- 7.00-12 6PR TL
- 10.0/75-15.3 10PR TL
- 10.0/75-15.3 10PR TT
- 10.0/75-15.3 12PR TL
- 10.0/75-15.3 12PR TT
- 10.0/75-15.3 14PR TT

- 10.0/75-15.3 18PR TL
- 10.0/75-15.3 12PR TL NEW
- 10.0/75-15.3 14PR TL
- 11.5/80-15.3 10PR TL
- 11.5/80-15.3 12PR TL
- 11.5/80-15.3 12PR TT
- 11.5/80-15.3 14PR TL
- 11.5/80-15.3 16PR TT

- 11.5/80-15.3 16PR TL
- 12.5/80-15.3 12PR TL
- 400/60-15.5 14PR TL
- 400/60-15.5 16PR TL
- 10.5/65-16 14PR TL
- 13.0/55-16 12PR TL
- 13.0/55-16 14PR TL
- 13.0/55-16 18PR TL

- 12.5/80-18 12PR TL
- 12.5/80-18 14PR TL
- 12.5/80-18 16PR TL
- 12.5/80-18 18PR TL
- 13.0/65-18 16PR TL

FARM IMPLEMENT 404

For Trailers & Implements



Multi rib low section design

High flotation with minimum soil compaction



Extra wide tread & high volume

High load carrying capacity



Non directional tread pattern

Prevents skidding while turning



Lugs are open & angled at the shoulder

Ensures maximum stability



Large contact area

Designs for both on & off-road application

SIZES

- 14.0/65-16 10PR TL
- 14.0/65-16 14PR TL
- 15.0/55-17 10 PR TL
- 15.0/55-17 14PR TL
- 15.0/55-17 26PR TL
- 500/50-17 10PR TL
- 500/50-17 14PR TL
- 15.0/70-18 16PR TL

FARM IMPLEMENT LP

For Implements



Advanced tread design

Long tyre life



Rounded shoulder

Reduces soil compaction



Multi-rib design

Effortless steering control



SIZES

- 16.5L-16.15L 10PR TL
- 16.5L-16.15 14PR TL

HIGHWAY IMPLEMENT T422

For Trailers



Higher land area

Uniform wear & longer tyre life



Heavily grooved ribs

Easy steering and overall stability of the equipment



Heavy carcass

Higher load carrying capacity



Specially designed compound

Suitable for higher speed



SIZES

▪ 11L-15FI F TL

▪ 12.5L-15FI F TL

▪ 9.5L-15FI D TL

FLOTATION PLUS

For Trailers



Larger volume & footprint

Reduces compaction



Rounded shoulder

Reduces damage to crops



SIZES

- 480/45-17 (19.0/45-17) 10PR TL
- 480/45-17 (19.0/45-17) 14PR TL
- 480/45-17 (19.0/45-17) 16PR TL
- 480/45-17 (19.0/45-17) 18PR TL
- 500/50-17 14PR TL

- 560/60-22.5 16PR TL
- 600/55-22.5 16PR TL
- 700/50-22.5 16PR TL
- 550/60-22.5 16TL

FLOTATION T422

For Trailers



Larger volume & footprint

Reduces compaction



Tough nylon casing, strong bead bundle

Improves performance on slopes



Rounded shoulder

Reduces damage to crops



SIZES

- 500/50-17 16PR TL
- 500/50-17 18PR TL
- 400/55-17.5 14PR TL
- 500/60-22.5 16PR TL
- 550/45-22.5 16PR TL
- 550/45-22.5 20PR TL
- 550/60-22.5 16PR TL
- 550/60-22.5 20PR TL
- 600/50-22.5 16PR TL
- 600/55-22.5 16PR TL
- 700/40-22.5 16PR TL
- 700/40-22.5 18PR
- 700/50-22.5 16PR TL
- 600/55-26.5 16PR TL
- 700/50-26.5 16PR TL
- 800/45-26.5 12PR TL
- 800/45-26.5 16PR TL

T422 VALUE PRO

For Trailers



Larger volume & footprint

Reduced compaction



Rounded shoulder

Reduced damage to crops



SIZES

- 400/60-15.5 16PR TL
- 400/60-15.5 20PR TL
- 400/55-22.5 12PR TL
- 400/55-22.5 16PR TL
- 400/55-22.5 20PR TL
- 400/55-22.5 18PR TL
- 500/45-22.5 12PR TL
- 500/45-22.5 16PR TL
- 500/60-22.5 16PR TL
- 550/45-22.5 16PR TL
- 550/60-22.5 16PR TL

FLOTATION TX440

For Trailers & Excavators



Larger volume & footprint

Reduces compaction



Rounded shoulder

Reduces damage to crops



SIZES

- 500/60-22.5 16PR TL
- 550/60-22.5 16PR TL
- 600/50-22.5 16PR TL
- 600/50-22.5 18PR TL
- 700/40-22.5 16PR TL
- 700/40-22.5 18PR TL

TR800

For Implements



Rounded shoulder

Reduces damage to crops



Larger volume & footprint

Reduces compaction



SIZES

- 400/60-15.5 14PR TL
- 400/60-15.5 18PR TL

IRROGATOR

For Irrigation Machines



Optimised lug angle with lug overlap

Uniform wear



Strong nylon casing

Excellent stability & increased service life



SIZES

- 11.2-24 4PR TT
- 14.9-24 6PR TL
- 11.2-38 6PR TT
- 11.2-24 6PR TL
- 14.9-24 8PR TT
- 11.2-38 6PR TL

TURF XL

For Turf & Utility Tractor



More rubber on the contact surface

Better performance in all soil and turf conditions



High tread depth

Better performance in all soil and turf conditions



Unique rounded shoulder block design

No turf damage and ease while turning



Enlarged contact area

Improves stability and traction



SIZES

- 16x7.50-8 4PR TL
- 23x8.50-12 6PR
- 26x12.00-12 8PR TL
- 13.6-16 4PR TL
- 26x12.00-12 4PR TL
- 24x8.5-14 4PR TL
- 23x10.50-12 8PR TL
- 26x12.00-12 10PR TL
- 25x8.5-14 6PR TL
- 23x8.50-12 4PR
- 26x12.00-12 12PR TL
- 38x14-20 4PR TL

LOGGER XL

For Forestry Log Skidder



Strong and straight lugs

High traction across all surfaces



Reinforced sidewall & shoulder deflector

Protection against impacts & cuts



Deep and open shoulder

Better self cleaning



Rim protector

Protects bead against stub damage



Multi-layer Nylon carcass with wide steel breakers

Excellent puncture resistance

SIZES

- 23.1-26 16PR TT STEEL SHIELD
- 28L-26 20PR TL
- 24.5-32 20PR TL STEEL SHIELD
- 30.5L-32 26PR TL
- 35.5L-32 26PR TL STEEL SHIELD

FOREST XL

For Forwarder & Harvester



Wide and robust Lug Design

Excellent traction & support for track use



Larger tread Width

Ensures wider footprint resulting in low ground pressure



Steel belted construction

Superior puncture resistance & load carrying capacity



Uniquely designed bead area

Prevents rim slippage



Specially designed tread and sidewall compound

Provides protection to the tyre from cuts & tears and durability in rough terrain



SIZES

- 710/45-26.5 20PR TL STEEL SHIELD
- 710/45-26.5 24PR TL STEEL SHIELD

GM LOADER HD

For Skid Steer



Higher tread depth with extra thick sidewall

Improves traction & puncture resistance



Strong nylon casing

Excellent durability



Specially designed rim guards

Greater protection of rim flange area



SIZES

- 27x10.50-15 8PR TL
- 10-16.5 10PR TL
- 12-16.5 12PR TL
- 12-16.5 14PR TL

GRIP X HD

For Skid Steer



Multi-use tread pattern

Heavy duty service



Extra deep tread

Long tyre life



Specially formulated compound

Cut & chip resistance



Strong nylon casing

Excellent durability



Specially designed rim guards

Greater protection of rim flange area



SIZES

- 10-16.5 12PR TL
- 12-16.5 14PR TL

GRIP XL 5

For Skid Steer



High abrasion-resistant compound

Enhances durability



Deep treads

Better longevity



Broad lugs

Superior stability and improved self-cleaning



Specially designed rim guard

Protection against flats and rim flange damage



Strong nylon casing

Improves lateral stability

SIZES

- 10-16.5 NHS 10PR TL
- 12-16.5 12PR TL

GRIP XL HARD SURFACE

For Skid Steer



Strong Nylon Casing

Enhances lateral stability and structural strength



Deep Tread Design

Provides improved traction across surfaces



Broad Lugs

Deliver excellent stability with efficient self-cleaning



Rim Guard Protection

Protects against flats and rim flange damage



SIZES

- 12-16.5 12PR TL

LOADER PRO HD

For Skid Steer



Solid centre lug with

Deep shoulders



Deeper tread depth

Excellent traction & puncture resistant



Strong nylon casing

Excellent durability



Step down lugs

Self cleaning



Rim guard

Cut & chip resistant



Skid steer for industrial & construction applications

Heavy duty service

SIZES

▪ 14-17.5 14PR TL

▪ 15-19.5 14PR TL

▪ 15-19.5 6PR TL

MPT 503

For Multipurpose Tractor & Telehandler



Special tread pattern

Excellent traction



Extra sidewall

Prevents sidewall damage



Tie bar

Enhances stability



Wider tread width

Better performance



SIZES

▪ 18-19.5 16PR TL

▪ 18-19.5 18PR TL

▪ 18-22.5 16PR TL

MPT 602

For Multipurpose Tractor, Excavator & Dumper



Wide diagonal lug design

Excellent traction & improved stability



Strong nylon casing

High load carrying capacity



Specially formulated compound

Heat, cut & weather resistance



SIZES

- 12.5-18 12PR TL
- 12.5-18 16PR TL
- 10.00-20 16PR TT
- 12.5-20 12PR TL
- 405/70-20 14PR TL
- 405/70-20 18PR TL
- 405/70-20 20PR TL
- 405/70-24 14PR TL
- 405/70-24 16PR TL

MPT 800

For Telehandler & Loader



Superior tread compound

Cut & chip resistance



Robust casing

Better lateral stability



SIZES

- 405/70-20 14PR TL
- 405/70-24 14PR TL
- 405/70-24 16PR TL

MPT 808

For Multipurpose Tractor & Telehandler



Specially designed wide lugs

Better self-cleaning



Superior tread compound

Resistant to tearing & cracking



Strong nylon casing

Higher strength and stability



SIZES

- 10.0/75-15.3 14PR TL
- 11.5/80-15.3 14PR TL
- 10.5-18 12PR TL
- 12.0/75-18 12PR TL
- 12.0-18 12PR TL
- 12.5-18 12PR TL
- 18-19.5 18PR TL
- 10.5-20 12PR TL
- 12.5-20 12PR TL
- 14.5-20 14PR TL
- 405/70-20 18PR TL

TYROCK

For Backhoe loader & Wheel Loader



Wider lugs

Offers excellent traction



Unique tread pattern

Specially designed for front wheel of Backhoe Loaders and Wheel Loaders



Strong Nylon Casing

High load carrying capacity



Industrial tread compound

Cut & chip resistance



SIZES

- 12.5/80-18 10PR TL
- 12.5/80-18 12PR IND TL
- 12.5/80-18 12PR IND TT
- 12.5/80-18 14PR IND TL
- 12.5/80-18 18PR IND TL
- 19.5L-24 10PR 80 TL
- 19.5L-24 12PR 80 TL
- 18.4-26 12PR R4 TL
- 18.4-26 14PR R4 TL
- 18.4-26 16PR R4 TL

TYROCK SUPER

For Backhoe loader & Telehandler



Open shoulders

Improves self-cleaning



Specially designed tread with heavy center mass

Heavy duty service



Large wide centre lugs

Excellent ground contact for maximum stability



Heat & cut resistant compound

Improves product life



SIZES

- 16.9-28 12PR TL
- 16.9-28 14PR TL
- 16.9-28 8PR TL
- 16.9-30 14PR TL

TYROCK SUPER X3

For Backhoe loader, Telehandler, Compact Utility Tractors



Specially designed tread with heavy center mass

Suitable for heavy duty service



Extra deep tread with special compound

Resistance to cuts and chipping
Higher durability



Extra deep tread

Higher Durability



SIZES

- 23X8.50-12 12PR TL
- 26x12.00-12 4PR TL
- 23X8.5-14 4PR TL
- 27X8.5-15 6PR TL
- 12.4-16 4PR TL
- 10.5/80-18 8PR TL
- 15-19.5 6PR TL
- 16.0/70-20 (400/70-20) 16PR TL
- 43x16.00-20 4PR TL
- 16.9-24 (440/80-24) 12PR TL
- 16.9-24 (440/80-24) 8PR TL
- 17.5L-24 8PR TL
- 17.5L-24 12PR TL
- 18.4-24 12PR TL
- 19.5L-24 12PR TL
- 440/80-24(16.9-24) 18PR TL
- 18.4-28 12PR TL
- 33X15.5-16.5 12PR TL
- 25X8.5-14 6PR TL

GRIP MASTER EX

For Excavator



Wide diagonal lug design

Excellent traction & Improves stability



Strong nylon casing

High load carrying capacity



Specially formulated compound

Heat, cut & weather resistance



SIZES

▪ 10.00-20 16PR TT E-2

▪ 11.00-20 16PR TT E-2

▪ 9.00-20 14PR TT E-2

GRADER XL

For Grader, Loader



Superior tread & sidewall compound

Heat, cut & weather resistant



Sturdy & robust tyre for the drive wheel application

Smooth & trouble-free service in severe conditions



Strong nylon casing

High loadability



SIZES

▪ 13.00-24 12PR G2/L2 TL

▪ 14.00-24 16PR G2 TL

▪ 17.5-25 24PR TL G2/L2

▪ 13.00-24 16PR G2/L2 TL

▪ 17.5-25 12PR G2/L2 TL

▪ 14.00-24 12PR G2/L2 TL

▪ 17.5-25 16PR G2/L2 TL

GRADER XL PLUS

For Grader, Loader



More number of lugs

Provides better traction



Strong carcass

Reduces mechanical failure



Specially formulated compound

Heat, cut & weather resistant



SIZES

- 13.00-24 16PR G2/L2 TT

GRIP MASTER-ND

For Grader Backhoe Loader, Dump Truck



Sturdy & robust tyre for the drive wheel application

Smooth & trouble-free service in severe conditions



Superior tread & sidewall compound

Heat, cut & weather resistant



Strong nylon casing

High loadability



SIZES

- 14.00-24 24PR E3 TT
- 14.00-24 28PR E3 TT
- 14.00-25 12PR L3 TT
- 14.00-25 20PR E3 TL
- 14.00-25 20PR E3 TT
- 14.00-25 20PR L3 TT
- 14.00-25 24PR E3 TT
- 18.00-25 32PR E3 TL
- 18.00-25 40PR E3 TL
- 14.00-24 28PR E3 IND TT
- 14.00-24 28PR E3 IND TT
- 18.00-25 40PR E3 IND TL

LOADER XL

For Loader



R4 tread pattern

Suitable on & off the road



Tough wide base

Excellent traction & handling response



Superior compound

Designed for crane & rescue vehicles



Strong nylon casing

Capable to run at high speeds



SIZES

- 15.5-25 12PR G2/L2 TL
- 17.5-25 12PR G2/L2 TL
- 17.5-25 16PR G2/L2 TL
- 17.5-25 16PR TL DUAL BEAD
- 17.5-25 24PR TL L2
- 17.5-25 G 16PR TL
- 20.5-25 12PR G2/L2 TL
- 20.5-25 16PR G2/L2 TL

TRAC XL

For Articulated Dump Truck & Loader



Wide centre lugs

Excellent ground contact for maximum stability



Non direction tread pattern

Excellent traction & grip



Specially formulated compound

Provides heat resistance & cut protection



SIZES

- 405/70-20 16PR TL
- 17.5-25 16PR E3/L3 TL
- 17.5-25 20PR E3/L3 TL
- 17.5-25 20PR E3/L3 TT
- 17.5-25 20PR E3/L3 TT
- 17.5-25 32PR E3/L3 TL
- 23.5-25 20PR E3/L3 TL
- 23.5-25 20PR E3/L3 TT
- 26.5-25 24PR TL
- 26.5-25 28PR E3/L3 TL
- 29.5-25 32PR E3/L3 TL
- 29.5-25 34PR

C305

For Compactor



Strong nylon casing & increased tread depth

Flat & wide footprint makes it suitable for industrial & road construction applications



Rugged design for multipurpose drive wheel tyre

Provides higher flotation on soft soil with minimum ground disturbance



High modulus compound

Longer service life in several operating conditions



SIZES

- 23.1-26 12PR R3 TL IND
- 23.1-26 16PR R3 TL IND
- 23.1-26 18PR TL DUAL BEAD

ROCK XL

For Dump Truck



Strong bead bundle

Minimised bead failure



Higher under tread

Resistance to puncture



Strong nylon casing

High load carrying capacity



Specially formulated compound

Resistance to cuts, snags & bruises



SIZES

- 16.00-25 32PR E3 IND TL
- 18.00-25 40PR E4 TL
- 18.00-25 40PR IND TL
- 21.00-25 40PR E4 TL
- 18.00-33 40PR E4 IND TL
- 18.00-33 40PR E4 TL
- 21.00-35 36PR E4 TL
- 24.00-35 48PR E4 TL
- 16.00-25 IND-3 32PR TL

GRIP MASTER XL

For Dump Truck



Extra deep tread & robust casing

Ideal for heavy duty application in mining, quarrying & rock excavation



Strong nylon casing

High load carrying capacity



Specially formulated compound

Heat, cut & weather resistance



SIZES

- 18.00-25 32PR E4 TL

PORT PRO RX

For Reach Stacker



Strong bead bundle

Minimised bead failure



Higher under tread

Resistance to puncture



Specially formulated compound

Resistance to cuts, snags & bruises



Strong nylon casing

High load carrying capacity



SIZES

- 18.00-25 40PR IND4 TL
- 18.00-33 40PR IND4 TL

PORT PRO TX

For RTG Crane



Larger footprint

High ground contact area with improved stability



Higher under tread

Resistance to puncture



Strong nylon casing

High load carrying capacity



Specially formulated compound

Resistance to cuts, snags & bruises



SIZES

▪ 18.00-25 40PR IND3 TL

▪ 21.00-25 40PR IND3 TL

▪ 21.00-35 40PR IND3 TL

PORT XL PLUS

For Reach Stacker



Better resistance to puncture and impact due to deep tread depth and under tread

Extra deep tread promotes longer life



Carries heavy loads under extreme working conditions

Special wear resistant compound gives extra life



Ideal for heavy duty application at ports and container handling application on hard and improved surfaces like concrete and asphalt

Can also be used for intermittent highway surface



SIZES

▪ 18.00-25 40PR IND4.5 TL

PORT PRO SL

For Reach Stacker



Flat tread with large width

Self cleaning properties



Specially formulated tread compound

High ground contact area for good traction on paved surface



Reinforced sidewall

Improves penetration resistance



SIZES

- 18.00-25 40PR IND4 TL
- 18.00-33 40PR IND4 TL
- 18.00-25 40PR IND5 TL
- 18.00-33 40PR IND5 TL

PORT PRO SS

For Reach Stacker



Wear-Resistant Compound

Special tread compound ensures longer tire life.



Heavy-Duty Nylon Casing

Boosts strength and durability while supporting multiple retreads with minimal downtime.



Wide Tread Design

Larger tread width increases ground contact for better traction on paved surfaces.



SIZES

- 18.00-25 40PR IND-4.5 TL

SLICK 404

For RTG Crane & Reach Stacker



Reinforced Sidewall

Long service life



Flatter & larger tread width

Higher ground contact area & traction



Specially formulated tread compound

Improves penetration and heat resistance



SIZES

▪ 14.00-24 28PR L55 IND TT

▪ 18.00-25 40PR L55 IND5 TL

SLICK 431

For RTG Crane



Reinforced Sidewall

Long service life



Flatter & larger tread width

Higher ground contact area & traction



Specially formulated tread compound

Improves penetration and heat resistance



SIZES

▪ 16.00-25 32PR L45 IND TL

ELEVETA X3

For Forklift



Non-directional deep tread

Better tyre life & heavy-duty material handling



Specially designed rim guard

Protects against wheel damages in the rim flange area



Tie bar at the center

Provides durability during application & uniform wear



Special tread compound

Better cut, chip & tear resistance, suitable for rough & hard concrete surfaces



SIZES

- 5.00-8 NHS 10PR TT
- 21X8-9 18PR TT
- 6.00-9 NHS 10PR TT
- 6.50-10 NHS 10PR TT
- 6.50-10 NHS 12PR TT
- 6.50-10 NHS 14PR TT
- 7.00-12 NHS 12PR TT
- 7.00-12 NHS 14PR TT
- 28X9-15(8.15-15) NHS 14PR TT
- 7.00-15 NHS 12PR TT
- 7.50-15 NHS 12PR TT
- 8.25-15 NHS 14PR TT
- 8.25-15 NHS 16PR TT
- 7.50-16 16PR TT
- 300-15 20PR TT
- 250-15 16PR TT
- 18X7-8 16PR TT

ELEVETA PLUS

For Heavy Duty Forklift



Non-directional deep tread

Better tyre life & heavy-duty material handling



Specially designed rim guard

Protects against wheel damages in the rim flange area



Tie bar at the center

Provides durability during application & uniform wear



Special tread compound

Better cut, chip & tear resistance, suitable for rough & hard concrete surfaces



SIZES

- 9.00-20 14PR TT
- 10.00-20 16PR TT
- 11.00-20 18PR TT
- 12.00-20 20PR TT
- 12.00-20 28PR TT

TRENCHER XL

For Tractor



Self-Cleaning Tread

Ensures better grip with efficient mud and debris clearance



Durable Tread Compound

Resists chipping and tearing for longer tire life



Multipurpose Use

Suitable for a wide range of applications



SIZES

- 16.5L-16.1SL 10PR TL

LOAD INDEX & SPEED SYMBOL

According to ETRTO (The European Tyre & Rim Technical Organization), as well as to ECE (Economic Commission for Europe-UN Institution Geneva), the maximum load capacity, as well as the maximum speed are indicated by load index & speed symbol.

The following table shows the meaning of each speed symbol & the load in kg/lbs corresponding to each load index:

Load Index	Load Kg / lbs	Load Index	Load Kg / lbs	Load Index	Load Kg / lbs	Load Index	Load Kg / lbs	Speed Symbol	Kmph / mph
102	850 / 1874	129	1850 / 4078	156	4000 / 8818	183	8750 / 19290	A1	5 / 3
103	875 / 1929	130	1900 / 4189	157	4125 / 9094	184	9000 / 19841	A2	10 / 6
104	900 / 1984	131	1950 / 4299	158	4250 / 9369	185	9250 / 20392	A3	15 / 9
105	925 / 2039	132	2000 / 4409	159	4375 / 9645	186	9500 / 20944	A4	20 / 12
106	950 / 2094	133	2060 / 4541	160	4500 / 9921	187	9750 / 21495	A5	25 / 16
107	975 / 2149	134	2120 / 4674	161	4625 / 10196	188	10000 / 22046	A6	30 / 19
108	1000 / 2205	135	2180 / 4806	162	4750 / 10472	189	10300 / 22707	A7	35 / 22
109	1030 / 2271	136	2240 / 4938	163	4875 / 10747	190	10600 / 23369	A8	40 / 25
110	1060 / 2337	137	2300 / 5071	164	5000 / 11023	191	10900 / 24030	B	50 / 31
111	1090 / 2403	138	2360 / 5203	165	5150 / 11354	192	11200 / 24691	C	60 / 37
112	1120 / 2469	139	2430 / 5357	166	5300 / 11684	193	11500 / 25353	D	65 / 40
113	1150 / 2535	140	2500 / 5511	167	5450 / 12015	194	11800 / 26014	E	70 / 44
114	1180 / 2601	141	2575 / 5677	168	5600 / 12346	195	12150 / 26786	F	80 / 48
115	1215 / 2679	142	2650 / 5842	169	5800 / 12787	196	12500 / 27557	G	90 / 56
116	1250 / 2756	143	2725 / 6007	170	6000 / 13228	197	12850 / 28329	J	100 / 62
117	1285 / 2833	144	2800 / 6173	171	6150 / 13558	198	13200 / 29101	K	110 / 68
118	1320 / 2910	145	2900 / 6393	172	6300 / 13889	199	13600 / 29982	L	120 / 75
119	1360 / 2998	146	3000 / 6614	173	6500 / 14330	200	14000 / 30864	M	130 / 81
120	1400 / 3086	147	3075 / 6779	174	6700 / 14771	201	14500 / 31966	N	140 / 87
121	1450 / 3197	148	3150 / 6944	175	6900 / 15212	202	15000 / 33069	P	150 / 93
122	1500 / 3307	149	3250 / 7165	176	7100 / 15653	203	15500 / 34171	Q	160 / 99
123	1550 / 3417	150	3350 / 7385	177	7300 / 16093	204	16000 / 35273	R	170 / 106
124	1600 / 3527	151	3450 / 7606	178	7500 / 16534	205	16500 / 36376	S	180 / 112
125	1650 / 3638	152	3550 / 7826	179	7750 / 17086	206	17000 / 37478		
126	1700 / 3748	153	3650 / 8047	180	8000 / 17637	207	17500 / 38580		
127	1750 / 3858	154	3750 / 8267	181	8250 / 18188	208	18000 / 39683		
128	1800 / 3968	155	3875 / 8543	182	8500 / 18739	209	18500 / 40785		



www.ceatspecialty.com