

GRADER XL

CEAT
SPECIALTY

FEATURE

Better Stability

BENEFIT

- Tyre with heavy duty carcass & more number of lugs
- Better stability & trouble free service in severe condition

FEATURE

Special Tread

BENEFIT

- Special tread design with heavy centre mass High load carrying capacity



FEATURE

Strong Nylon Casing

BENEFIT

- Strong nylon casing Improved durability & high load carrying capacity

FEATURE

Superior Tread

BENEFIT

- Superior tread & sidewall compound
- Heat, cut & weather resistant

LIST OF SIZES

SIZE	SR
13.00 - 24	582
14.00 - 24	614
17.5-25	614

All tyres conform to ETRTO & TRA standards.



Size	PR	Type	Rim Width in	Flange Height in	SW	OD	Static Loaded Radius	Rolling Circum	GRADER SERVICE		LOADER SERVICE	
					mm/in	mm/in	mm/in	mm/in	40kmph / (25mph)	10kmph / (5mph)		
									Max Load	Infl. Prs.	Max Load	Infl. Prs.
									kg	bar	kg	bar
									lbs	psi	lbs	psi
17.5-25	24	TL	14	1.5	445 18	1348 53	614 24	3990 157	6000	5	9250	6.75
									13220	73	20390	98
	16	TL							3350	3.0	7300	4.7
									7400.0	43	16100	69
	12	TL							2900	2.0	6150	3.5
									6400	29.0	13600	51
14.00 - 24	16	TL	8.00	1.4	362 14.3	1348 53.1	614 24.2	3990 157.1	3650	3.5	7300	5.5
									8050	51	16090	80
	12	TL							3075	2.5	6300	4.25
									6800	36.0	13890	62
13.00 - 24	16	TL	8.00	1.4	333 13.1	1278 50.3	582 22.9	3783 148.9	3250	3.8	6500	6.0
									7165	54.0	14300	87
	12	TL							2725	3.0	5600	4.5
									6000	44.0	12350	65

