

LIFT PRO

CEAT
SPECIALTY

WITH THE POWER OF CTR*

FEATURE

- Unique R1 pattern

BENEFIT

- Excellent traction



FEATURE

- Deep under tread

BENEFIT

- Improved puncture protection

FEATURE

- Strong nylon casing and thick sidewall

BENEFIT

- High radial and lateral stability

LIST OF SIZES

SIZE	LI/SS
460 70 R 24	159 A8/B

All tyres conform to ETRTO & TRA standards. Sizes available as of 07/2021.

LIST OF SIZES

SIZE	LI/SS
15.5/80-24	163A6
460/70R24	159AB/B



Size	PR	Type	Load, Speed Symbol Free Rolling	Drive Wheel	Rim Width in	Unloaded Dimension		Static Loaded Radius	Rolling Circum	Infl. Prs.	Load Capacity		
						SW	OD				Max Speed	Max Load	
												Free Rolling	Drive Wheel
mm/in	mm/in	mm/in	mm/in	bar	kmph	kg	kg						
										psi	mph	lbs	lbs
15.5/80-24	16	TL	163 A6	151 A6	13.00	395	1250	562	3650	4	30	4875	3450
						15.5	49.2	21.5	144	58	20	10745	7600

Size	Rim	Infl tire dimension		Static Loaded radius	Rolling circm.	Load Index	Infl. press.	Recommend load, kg (lbs)							
		Speed, km/h (mph)													
		SW	OD	mm/in	mm/in	Speed	bar	Constant load					Cyclic operation		
		mm/in	mm/in					Static	10	20	30	40	50	10	15
									6	12	19	25	31	6	9
460/70 R24	W15L, W16L, W14L	455 17.9	1254 49.4	566 22.3	3713 146	159A8/ B	0.8	3930	2140	1860	1780	1710	1710	2570	2290
							12	8660	4710	4100	3920	3770	24795	5660	5040
							1.6	5890	3200	2790	2660	2560	2560	3840	3430
							23	12970	7050	6150	5860	5640	37120	8460	7560
							2.8	8170	4440	3870	3690	3550	3550	5330	4760
							41	18000	9780	8520	8130	7820	51475	11740	10480
							3.2	8830	4800	4190	3990	3840	3840	5760	5150
							46	19450	10570	9230	8790	8460	55680	12690	11340
							4	10060	5470	4770	4550	4375	4375	6560	5860
							58	22160	12050	10510	10020	9640	63437.5	14450	12910

