

MPT 808

CEAT
SPECIALTY

FEATURE

Strong nylon casing

BENEFIT

Higher strength
and stability

FEATURE

Specially designed
wide lugs

BENEFIT

Better self-cleaning

FEATURE

Superior tread
compound

BENEFIT

Resistance to
tearing & cracking



LIST OF SIZES

SIZE	LI/SI
10.0/75-15.3	130 A8(FR)/ 118 A8(DW)
10.5-18	134B
10.5-20	135 B
11.5/80-15.3	139 A8(FR)/ 126 A8(DW)
12.0-18	145 A6
12.0/75-18 (300/75-18)	139 A8 (FR)/126A8(DW)
12.5-18	135 B
12.5-20	140 B
14.5-20	143 B
18-19.5	165 B

All tyres conform to ETRTO & TRA standards. Sizes available as of 12/2021.



Size	LI/SS	PR	Rim	Unloaded Dimension		SLR	RC	Load Carrying Capacity		
				SW	OD			Infl. Pre	Max. Speed	Max Load
				mm/in	mm/in	mm/in	mm/in	bar	Kmph	kg
								psi	mph	lbs
10.0/75-15.3	130 A8 (FR)/ 118 A8 (DW)	14	9x15.3	260	775	365	2400	5.5	40	1900 / 1320
				10.2	30.5	14.4	94.5	79	25	4190 / 2910
10.5-18	134B	12	9 x 18	270	905	400	2690	4.5	50	2120
				10.6	35.6	15.7	105.9	65	31	4670
10.5-20	135 B	12	9x20	270	955	445	2880	4.3	50	2180
				10.6	37.6	17.5	113.4	62	30	4810
11.5/80-15.3	139 A8 (FR)/ 126 A8 (DW)	14	9x15.3	292	870	395	2580	4.75	40	2430 / 1700
				11.5	34.3	15.6	101.6	69	25	5355 / 3745
12.0-18	145 A6	12	W9x18	295	930	430	2775	4.5	30	2900
				11.6	36.6	16.9	109.2	65	19	6395
12.0/75-18 (300/75-18)	139 A8 (FR) /126 A8 (DW)	12	W9x18	295	915	427	2755	4	40	2430 / 1700
				11.6	36.1	16.8	108.4	58	25	5355 / 3745
12.5-18	135 B	12	11x20	325	990	450	2940	3.5	50	2180
				12.8	39	17.7	115.7	51	30	4810
12.5-20	140 B	12	11x20	325	1040	475	3090	4	50	2500
				12.8	40.9	18.7	121.7	58	30	5510
14.5-20	143 B	14	11x20	355	1098	505	3260	3.5	50	2725
				14	43.2	19.9	128.3	51	30	6010
18-19.5	165 B	18	11x20	457	1110	503	3227	7.25	50	5150
				18	44	20	127	105	30	11354

All tires confirms ETRTO T&RA & STRO standards

