

PORT PRO SL

CEAT
SPECIALTY

WITH THE POWER OF CTR*

FEATURE

Flat tread with large width

BENEFIT

Self cleaning properties

FEATURE

Specially formulated tread compound

BENEFIT

High ground contact area for good traction on paved surface

FEATURE

Reinforced sidewall

BENEFIT

Improved penetration resistance



LIST OF SIZES

SIZE	LI/SS
18.00-33	862
18.00-25	768
18.00-25	768

All tyres conform to ETRTO & TRA standards.



Size	PR	Type	Rim Width in	Flange Height in	Unloaded Dimension		Static Loaded Radius	Rolling Circum		Load Capacity					
					SW	OD			Infl. Prs.	25 kmph (15mph)	10 kmph (5mph)	5 kmph (3mph)	1 kmph (0.6mph)	Static	
										Max Load	Max Load	Max Load	Max Load	Max Load	
										bar	kg	kg	kg	kg	kg
										psi	lbs	lbs	lbs	lbs	lbs
18.00-33	40	TL	13.00	2.5	498	1877	862	5556	11.4	25000	27000	29000	32000	36000	
					20	74	34	219	165	55000	59400	63800	70400	79200	
18.00 - 25	40	TL	13.00	2.5	498	1673	768	4952	10	21250	22950	24650	27200	30600	
					20	66	30	195	145	46845	50595	54345	59965	67460	
18.00 - 25	40	TL	13.00	2.5	498	1673	768	4952	10.5	21250	22950	24650	27200	30600	
					20	66	30	195	150	46845	50595	54345	59965	67460	

All tyres conform to ETRTO & TRA standards.

