FEATURES AND BENEFITS

IF Construction

Carry heavier load at low inflation pressure

Steel belt at crown

Puncture resistance

Rounded Shoulder

Excellent self-cleaning capabilities

Reinforced sidewall & bead

Longer tyre life

*Designed for steering & drive wheel applications

HI-FLEX IMPLEMENT

HI-FLEX IMPLEMENT

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)			
		SW	OD					Speed, km/h (mph)			
		mm/in	mm/in	mm/in	mm/in	Speed	bar	10	20	30	40 to 65km/H
						Symbol	psi	6	12	19	25 to 40mph
IF 320/70 R15	10LB	320	829	364	2461	146D	0.8	1140	970	940	900
							12	2510	2140	2070	1980
							2	2030	1730	1660	1600
							29	4470	3810	3660	3520
		12.6	32.6	14.3	96.9		3.0	2630	2240	2150	2070
							44	5790	4930	4740	4560
							4	3260	2780	2670	2570
							58	7180	6120	5880	5660
							5.2	3810	3240	3120	3000
							75	8390	7140	6870	6610

Size	Rim	Unloaded dimension		Static Loaded Radius	Rolling Circum	Load Index	Infl. press.	maximum load, kg (lbs)			
		SW	OD					Speed, km/h (mph)			
		mm/in	mm/in	mm/in	mm/in	Speed	bar	10	20	30	40 to 65km/H
						Symbol	psi	6	12	19	25 to 40mph
IF 280/70 R15	8LB W8	280 11.0	773	342	2295	137D	0.8	970	820	790	760
							12	2140	1810	1740	1670
							2	1700	1450	1390	1340
							29	3740	3190	3060	2950
			30.4	13.5	90.3		3.0	2160	1840	1770	1700
							44	4760	4050	3900	3740
							4	2630	2240	2150	2070
							58	5790	4930	4740	4560
							4.8	2920	2480	2390	2300
							70	6430	5460	5260	5070