

TYROCK SUPER X3

Construcción e Industrial



Manipulador telescópico

Cargadora retroexcavadora



1 (Banda de rodadura especialmente diseñada con masa central pesada) Apta para servicio pesado

2 (Grandes orejetas centrales anchas) Buena estabilidad
Autolimpieza

3 (Banda de rodadura extra profunda con compuesto especial)
Resistencia a cortes y astillas
Mayor durabilidad

Sizes

Size	Rim
10.5/80-18	W9X18
15-19.5	11.75 X 19.5
43X16.00-20	W14Lx20
12.4-16	10LB
27X8.5-15	7JA X145
23X8.5-14	7JA X14
18X8.50-10	7.00 I - 55 ; I - 70
26x12-12	10.50 I - 55 ; I - 70
23x8.50-12	7.00 x 12
340/80-18 (12.5/80-18)	11
440/80-24 (16.9-24)	W15L
440/80-24 (16.9-24)	W15L
440/80-24 (16.9-24)	W15L
17.5L-24	W15L
17.5L-24	W15L
400/70-20	W13

18.4-24	W16L
18.4-28	DW 16 L
19.5L-24	DW 16 L
27x10.5-15	8LB

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD						Constant Load				
		mm	mm						Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
10.5/80-18	W9X18	280 11	910 36	400 16	2700 106	8PR 8PR	125 A8	2.8	3930	2060	1800	1720	1650
								41	8660	4540	3960	3790	3630

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Inflation Pressure	Recommended load,kg (lbs)				
								Speed,km/h(mph)				
		SW	OD					Constant Load				
		mm	mm					Static	10	20	30	40
		in	in	in	in	in	psi	Static	6	12	19	25
15-19.5	11.75 X 19.5	395 16	1030 41	465 18	3045 120	14PR 14PR	2.1	4420	2800	2130	1900	1760
							30	9740	6170	4690	4190	3880

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD						Constant Load				
		mm	mm						Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
43X16.0 0-20	W14Lx 20	400 16	1100 43	470 19	3270 129	4PR 4PR	133 A2	1.4	3250	2060	1570	1400	1300
								20	7160	4540	3460	3080	2860

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD						Constant Load				
		mm	mm						Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
12.4-16	10LB	320 13	970 38	426 17	2880 113	6PR 6PR	101A8	1.4	2260	1190	1040	990	950
								20	4980	2620	2290	2180	2090

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD						Constant Load				
		mm	mm						Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
12.4-16	10LB	320 13	970 38	426 17	2880 113	6PR 6PR	101A8	1.4	2260	1190	1040	990	950
								20	4980	2620	2290	2180	2090

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD						INDUSTRIAL TRACTOR				
		mm	mm						Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
27X8.5-15	7JA X145	218 9	693 27	310 12	2060 81	6PR 6PR	112 A2	3.1	1770	1120	850	760	710
								45	3900	2470	1870	1670	1560

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD						INDUSTRIAL TRACTOR				
		mm	mm						Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
23X8.5-14	7JA X14	205 8	598 24	270 11	1780 70	4PR 4PR	94 A2	2.4	1060	670	510	460	420

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD	Constant Load									
		mm	mm	mm	mm	mm	mm	bar	Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
18X8.50-10	7.00 I - 55 ; I - 70	210 8	460 18	220 9	1370 54	4PR 4PR	74 A2	1.5	590	375	290	260	240
								22	1300	830	640	570	530

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD	Constant Load									
		mm	mm	mm	mm	mm	mm	bar	Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
26x12-12	10.50 I - 55 ; I - 70	307 12	648 26	290 11	1920 76	4PR 4PR	100 A2	1.4	1260	800	610	540	500
								20	2780	1760	1340	1190	1100

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)				
									Speed,km/h(mph)				
		SW	OD	INDUSTRIAL TRACTOR									
		mm	mm	mm	mm	mm	mm	bar	Static	10	20	30	40
		in	in	in	in	in	in	psi	Static	6	12	19	25
340/80-18 (12.5/80-18)	11	350 14	1015 40	440 17	3010 119		143 A8	4.0	1260	800	610	540	2725
								58	2780	1760	1340	1190	6000

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommen load,kg (lbs)					
									Speed,km/ h(mph)					
		SW	OD						Constant Load					
		mm	mm						mm	mm	mm	mm	bar	40
		in	in						in	in	in	in	psi	25
440/80-24 (16.9-24)	W15L	438 17	1310 52	590 23	3805 150	8PR 8PR	142 A8	2.0	2650					
								29	5840					

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
440/80-24 (16.9-24)	W15L	438 17	1310 52	590 23	3805 150	12PR 12PR	149 A8	2.6	3250
								38	7160

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
440/80-24 (16.9-24)/3	W15L	438 17	1310 52	590 23	3805 150	18PR 18PR	162 A8	4.0	4750
								58	10460

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
17.5L-24	W15L	445 18	1252 49	560 22	3700 146	8PR 8PR	139 A8	1.9	2430
								27	5350

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
17.5L-24	W15L	445 18	1252 49	560 22	3700 146	12PR 12PR	146 A8	2.6	3000
								38	6610

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25

400/70-20	W13	395 16	1075 42	492 19	3228 127	16PR 16PR	144 A8	3.2	2800
								46	6170

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
18.4-24	W16L	475 19	1375 54	612 24	4116 162	12PR 12PR	155 A8	2.5	3875
								36	8540

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
18.4-28	DW 16 L	472 19	1475 58	620 24	4380 172	12PR 12PR	157 A8	2.5	4125
								36	9090

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
19.5L-24	DW 16 L	485 19	1314 52	560 22	3900 154	12PR 12PR	151 A8	2.3	3450
								33	7600

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
27x10.5-15	8LB	259 10	691 27	330 13	2110 83	8PR 8PR	105 A8	4.2	925
								61	2040