

FLOTATION T422



Landwirtschaft



Anhänger

Vorurteil



1 (Größeres Volumen und Fläche)

Reduzierte Verdichtung

2 (Abgerundete Schulter)

Reduzierte Bodenstörung

3 (Hohe Traglast) Robustes

Nylongehäuse, Starke Wulstbündel

4 (Größeres Volumen und Fläche)

Verringerte Verdichtung

Sizes

Size	Rim
400/60-15.5	13
550/45-22.5	16.00DC
550/45-22.5	16.00DC
550/45-22.5	16.DC
500/60-22.5	16.00DC
500/60-22.5	16.00DC
600/50-22.5	20.00DC
600/50-22.5	20.00DC
600/55-22.5	20.00DC
600/55-22.5	20.00DC
600/55-26.5	20.00DC
600/55-26.5	20.00DC
700/40-22.5	24.00DC
700/40-22.5	24.00DC
700/50-22.5	24.00DC
700/50-22.5	24.00DC

700/50-26.5	24.00DC
700/50-26.5	24.00DC
800/45-26.5	16.00DC
800/45-26.5	16.00DC
400/55-17.5	AG11.75
400/55-22.5	13.00DC

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD	Free Rolling					
		mm	mm	mm	mm	mm	mm	bar	40
		in	in	in	in	in	in	psi	25
400/60-15.5	13	400 16	876 35	385 15	2575 101	16PR 16PR	148 A836 A8	4.4	3150
								64	6940

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)			
									Speed,km/h(mph)			
		SW	OD						Constant Load			
		mm	mm						mm	mm	bar	40
		in	in						in	in	in	in
550/45-22.5	16.00DC	550 22	1070 42	470 19	3205 126	12 12		2.1	3650			
								2575	30			
								8048	5678			

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)			
									Speed,km/h(mph)			
		SW	OD						Constant Load			
		mm	mm						mm	mm	bar	40
		in	in						in	in	in	in
550/45-22.5	16.00DC	550 22	1070 42	470 19	3205 126	16 16		2.8	4375			
								3075	41			
								9647	6780			

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure					
		Recommen ded load,kg (lbs)	Speed,km/h (mph)										
		SW	OD							mm	mm	mm	mm
		mm	mm						bar	in	in	in	in
in	in	psi	550/45-22.5/3	16.DC	550 22	1070 42	470 19	3205 126					

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
500/60-22.5	16.00DC	500 20	1170 46	510 20	3380 133	12 12		2.4	4125
								2900	35

								9096	6395
								3.2	4875
								3450	46
								10749	7607

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
500/60-22.5	16.00DC	550 22	1238 49	540 21	3720 146	12 12		bar	25
								psi	40
								2.3	4500
								3150	33
								9923	6946
								3.0	5600
								3875	44
								12348	8544

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
600/50-22.5	20.00DC	600 24	1170 46	510 20	3498 138	12 12		bar	25
								psi	40
								2.2	4375
								29	9647
								2.6	5150
								38	11356

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
600/50-22.5	20.00DC	600 24	1170 46	510 20	3498 138	16 16		bar	25
								psi	40
								2.2	3075
								29	6780
								2.6	3650
								38	8048

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40

		in	in	in	in	in	in	psi	25
600/55-22.5	20.00DC	600 24	1238 49	540 21	3715 146	12 12		2.2	5000
								29	11025
								2.6	5800
								38	12789

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in					bar	40
								psi	25
600/55-22.5	20.00DC	600 24	1238 49	540 21	3715 146	16 16		2.2	3450
								29	7607
								2.6	4000
								38	8820

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in					bar	40
								psi	25
600/55-26.5	20.00DC	600 24	1333 52	585 23	3986 157	12 12		2.0	5150
								29	11356
								2.6	6000
								38	13230

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in					bar	40
								psi	25
600/55-26.5	20.00DC	600 24	1333 52	585 23	3986 157	16 16		2.0	3650
								29	8048
								2.6	4375
								38	9647

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in					bar	40
								psi	25

700/50-26.5	24.00DC	700 28	1333 52	585 23	3986 157	12 12		1.8	5800
								26	12789
								2.4	6700
								35	14774

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
700/50-26.5	24.00DC	700 28	1333 52	585 23	3986 157	16 16		1.8	4125
								26	9096
								2.4	4750
								35	10474

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
800/45-26.5	16.00DC	800 31	1343 53	585 23	4016 158	12 12		1.7	6000
								25	13230
								2.2	7300
								32	16097

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommened load,kg (lbs)
		SW	OD						Speed,km/h(mph)
		mm	mm						Constant Load
		in	in						40
800/45-26.5	16.00DC	800 31	1343 53	585 23	4016 158	16 16		1.7	4250
								25	9371
								2.2	5000
								32	11025

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure	Recommended load,kg (lbs)									
									Speed,km/h(mph)									
		SW	OD						Free Wheel		Drive Wheel							
		mm	mm						mm	mm	mm	mm	bar	40	50	bar	40	50
		in	in						in	in	in	in	psi	25	31	psi	25	31
400/55-17.5	AG11.7 5	375 15	887 35	420 17	2730 107	18 18		4.6	3550	3150	4.6	2430	2180					
								67	7828	6946	67	5358	4807					

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	Flange Height	Inflation Pressure
		Recommen ded load,kg (lbs)	Speed,km/h (mph)					
		SW	OD		mm	mm	mm	mm
		mm	mm	bar	in	in	in	in
in	in	psi	400/55-22.5	13.00DC	375 15	1060 42	494 19	3205 126