

MPT 602

Bau & Industrie



MPT

Vorurteil



1 (BESONDERHEIT) On- und Off-Road-Service, Breite diagonale Laschen, Mehrzweckmuster

2 (NUTZEN) Selbstreinigend, Beständig gegen seitliches Verrutschen, Hervorragende Traktion bei allen Wetter- und Betriebsbedingungen

Sizes

Size	Rim
10.00-20	7.5
405/70-20 (16.0/70-20)	13
405/70-20 (16.0/70-20)	13
405/70-20 (16.0/70-20)	13
405/70-24 (16.0/70-24)	13
405/70-24 (16.0/70-24)	13
12.5-18	11
12.5-18	11
12.5-20	11

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						50
		in	in						31
10.00-20	7.5	280 11	1069 42	497 20	3260 128	16PR 16PR	146 B	7.5	3000
								109	6610

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						50
		in	in						31
405/70-20 (16.0/70-20)	13	405 16	1085 43	505 20	3225 127	14PR 14PR	149 B	3.5	3250
								51	7160

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						50
		in	in						31
405/70-20 (16.0/70-20)	13	405 16	1085 43	505 20	3225 127	20PR 20PR	170B	6.5	6000
								94	13220

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						50
		in	in						31
405/70-20 (16.0/70-20)/3	13	405 16	1085 43	505 20	3225 127	18PR 18PR	165B	5.8	5150
								83	11340

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommened load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						50
		in	in						31

