

TYROCK SUPER

Budownictwo i Przemysł



Manipulator teleskopowy

Uprzedzenie



1 (Dodatkowo szerokie guzki)

Doskonała odporność na
rozerwanie i pękanie

2 (Otwarte barki) Poprawiona
samooczyszczalność

**3 (Specjalnie zaprojektowany
bieżnik z dużą masą środkową)**
Usługa o dużej wytrzymałości

4 (Duże szerokie guzki środkowe)
Doskonały kontakt z podłożem dla
maksymalnej stabilności

**5 (Związek odporny na ciepło i
cięcie)** Poprawiona trwałość
produktu

Sizes

Size	Rim
16.9-28	W15L
16.9-28	W15L
16.9-28	W15L
16.9-30	W15L

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
16.9-28	W15L	429 17	1435 57	672 27	4305 170	8PR 8PR	135 A8	3.0	3875
								44	8540

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
16.9-28	W15L	429 17	1435 57	672 27	4305 170	8PR 8PR	135 A8	3.0	3875
								44	8540

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
16.9-28	W15L	429 17	1435 57	672 27	4305 170	12PR 12PR	143 A8	1.9	2900
								28	6390

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25
16.9-28	W15L	429 17	1435 57	672 27	4305 170	12PR 12PR	143 A8	1.9	2900
								28	6390

Size	RIM	Inflated Tire Dimension		SLR	RC	PR	LI/SS	Inflation Pressure	Recommended load,kg (lbs)
									Speed,km/h(mph)
		SW	OD						Constant Load
		mm	mm						40
		in	in						25

