

FARMAX R65



Agriculture



Tractor

Radial



1 (R1 W tread depth) Longer tire life

2 (Tilted lug tip) Lesser vibration and noise

3 (Lower angle at shoulder)
Superior traction

4 (Mud breaker) Better self cleaning

5 (Rounded shoulder) Reduced damage to soil and crop

6 (Higher angle and lug overlap at center) Better roadability

7 (Reduced soil compaction) Wider tread, Larger inner volume

Sizes

Size	Rim
480/65R28	W15L
480/65R28	W15L
540/65R24	W16L
540/65R24	W16L
540/65R34	W16L
540/65R34	W16L
540/65R38	W16L
540/65R38	W16L
600/65R28	DW20B
600/65R28	DW20B
600/65R30	DW20B
600/65R30	DW20B
600/65R34	DW20B
600/65R34	DW20B
600/65R38	DW20B
540/65R26	W16L

320/65R16	W10
320/65R18	W10
340/65R18	W11
340/65R20	W11
420/65R20	W13
420/65R24	W13
440/65R20	W14L
440/65R24	W14L
440/65R24	W14L
440/65R28	W14L
480/65R24	W15L
480/65R24	W15L

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
480/65 R28	W15L W14L	479 18.9	1335 52.6	606 23.9	4068 160.2	142D	0.8	1710	1770	1630	1560	1490	1.0	2530	2310
							12	3770	3900	3590	3440	3280	15	5570	5090
							1.2	2170	2240	2070	1980	1890	1.5	3210	2930
							17	4780	4930	4560	4360	4160	22	7070	6450
							1.8	2760	2840	2630	2520	2400	2.3	4080	3720
							26	6080	6260	5790	5550	5290	33	8990	8190
							2.4	3050	3140	2900	2780	2650	3.0	4510	4110
							35	6720	6920	6390	6120	5840	44	9930	9050

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		Speed,km/h(mph)													
		SW	OD	Non-Cyclic Operation				Cyclic Operation							
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
480/65 R28	W15L W14L	479 18.9	1335 52.6	606 23.9	4068 160.2	136D	0.8	1710	1770	1630	1560	1490	1.0	2530	2310
							12	3770	3900	3590	3440	3280	15	5570	5090
							1.0	1960	2010	1860	1790	1700	1.3	2890	2640
							15	4320	4430	4100	3940	3740	18	6370	5810
							1.3	2280	2350	2170	2080	1980	1.6	3370	3070
							19	5020	5180	4780	4580	4360	24	7420	6760
							1.6	2580	2650	2450	2350	2240	2.0	3810	3470
							23	5680	5840	5400	5180	4930	29	8390	7640

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
		Speed,km/h(mph)													
		SW	OD	Non-Cyclic Operation				Cyclic Operation							
		mm	mm	mm	mm	mm	bar	Field Oper ation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Oper ation	16	25	31	40	psi	6	9
540/65 R24	W16L W18L	550 21.7	1312 51.7	590 23.2	3879 152.7	140D	0.8	1920	1980	1830	1750	1670	1.0	2840	2590
							12	4230	4360	4030	3850	3680	15	6260	5700
							1.0	2190	2250	2080	2000	1900	1.3	3230	2950
							15	4820	4960	4580	4410	4190	18	7110	6500
							1.3	2540	2620	2420	2320	2210	1.6	3760	3430
							19	5590	5770	5330	5110	4870	24	8280	7560
							1.6	2880	2960	2740	2630	2500	2.0	4250	3880
23	6340	6520	6040	5790	5510	29	9360	8550							

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15

		in	in	in	in	in	psi	Field Opera tion	16	25	31	40	psi	6	9
540/65 R24	W16L W18L	550 21.7	1312 51.7	590 23.2	3879 152.7	146D	0.8	1920	1980	1830	1750	1670	1.0	2840	2590
							12	4230	4360	4030	3850	3680	15	6260	5700
							1.2	2430	2500	2310	2220	2110	1.5	3590	3270
							17	5350	5510	5090	4890	4650	22	7910	7200
							2.0	3110	3200	2960	2840	2700	2.5	4590	4190
							29	6850	7050	6520	6260	5950	36	10110	9230
							2.4	3450	3560	3290	3150	3000	3.0	5100	4650
							35	7600	7840	7250	6940	6610	44	11230	10240

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Opera tion	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Opera tion	16	25	31	40	psi	6	9
540/65 R34	W16L W18L	550 21.7	1566 61.7	717 28.2	4659 183.4	145D	0.8	2220	2290	2110	2030	1930	1.0	3280	2990
							12	4890	5040	4650	4470	4250	15	7220	6590
							1.0	2530	2610	2410	2310	2200	1.3	3740	3410
							15	5570	5750	5310	5090	4850	18	8240	7510
							1.3	2960	3050	2810	2700	2570	1.6	4370	3980
							19	6520	6720	6190	5950	5660	24	9630	8770
							1.6	3340	3440	3180	3050	2900	2.0	4930	4500
							23	7360	7580	7000	6720	6390	29	10860	9910

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Opera tion	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Opera tion	16	25	31	40	psi	6	9
540/65 R34	W16L W18L	550 21.7	1566 61.7	717 28.2	4659 183.4	152D	0.8	2220	2290	2110	2030	1930	1.0	3280	2990
							12	4890	5040	4650	4470	4250	15	7220	6590
							1.2	2730	2810	2600	2490	2370	1.5	4030	3670
							17	6010	6190	5730	5480	5220	22	8880	8080
							1.8	3450	3560	3290	3150	3000	2.3	5100	4650
							26	7600	7840	7250	6940	6610	33	11230	10240
							2.4	4080	4210	3890	3730	3550	3.0	6040	5500
							35	8990	9270	8570	8220	7820	44	13300	12110

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Opera tion	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Opera tion	16	25	31	40	psi	6	9
540/65 R38	W16L W18L	550 21.7	1667 65.6	767 30.2	4975 195.9	147D	0.8	2350	2420	2230	2140	2040	1.0	3470	3160
							12	5180	5330	4910	4710	4490	15	7640	6960
							1.0	2680	2760	2550	2450	2330	1.3	3960	3610

							15	5900	6080	5620	5400	5130	18	8720	7950
							1.4	3270	3370	3110	2980	2840	1.8	4830	4400
							20	7200	7420	6850	6560	6260	25	10640	9690
							1.6	3540	3640	3370	3230	3075	2.0	5230	4770
							23	7800	8020	7420	7110	6770	29	11520	10510

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
540/65 R38	W16L W18L	550 21.7	1667 65.6	767 30.2	4975 195.9	153D	0.8	2350	2420	2230	2140	2040	1.0	3470	3160
							12	5180	5330	4910	4710	4490	15	7640	6960
							1.2	2990	3080	2850	2730	2600	1.5	4420	4030
							17	6590	6780	6280	6010	5730	22	9740	8880
							2.0	3770	3890	3590	3440	3280	2.2	5580	5080
							29	8300	8570	7910	7580	7220	32	12290	11190
							2.4	4200	4330	4000	3830	3650	3.0	6210	5660
							35	9250	9540	8810	8440	8040	44	13680	12470

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
600/65 R28	DW20 B W18L	611 24.1	1491 58.7	668 26.3	4473 176.1	154D	0.8	2370	2440	2260	2160	2060	1.0	3500	3190
							12	5220	5370	4980	4760	4540	15	7710	7030
							1.4	3340	3440	3180	3050	2900	1.8	4930	4500
							20	7360	7580	7000	6720	6390	26	10860	9910
							2.0	4120	4240	3920	3760	3580	2.5	6090	5550
							29	9070	9340	8630	8280	7890	36	13410	12220
							2.4	4310	4440	4110	3940	3750	3.0	6380	5810
							35	9490	9780	9050	8680	8260	44	14050	12800

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
600/65 R28	DW20 B W18L	611 24.1	1491 58.7	668 26.3	4473 176.1	147D	0.8	2350	2420	2230	2140	2040	1.0	3470	3160
							12	5180	5330	4910	4710	4490	15	7640	6960
							1.0	2680	2760	2550	2450	2330	1.3	3960	3610
							15	5900	6080	5620	5400	5130	19	8720	7950
							1.3	3130	3220	2980	2860	2720	1.6	4620	4220
							19	6890	7090	6560	6300	5990	23	10180	9300
							1.6	3540	3640	3370	3230	3075	2.0	5230	4770
							23	7800	8020	7420	7110	6770	29	11520	10510

		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
600/65 R34	DW20 B W18L	591 23.3	1644 64.7	780 30.7	4916 193.5	157D	0.8	2650	2730	2520	2420	2300	1.0	3910	3570
							12	5840	6010	5550	5330	5070	15	8610	7860
							1.2	3170	3270	3020	2900	2760	1.5	4690	4280
							17	6980	7200	6650	6390	6080	22	10330	9430
							1.5	3610	3720	3440	3300	3140	1.9	5340	4870
							22	7950	8190	7580	7270	6920	27	11760	10730
							2.0	4270	4400	4060	3900	3710	2.5	6310	5750
							29	9410	9690	8940	8590	8170	36	13900	12670
							2.4	4740	4890	4520	4330	4125	3.0	7010	6390
							35	10440	10770	9960	9540	9090	44	15440	14070

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
		Speed,km/h(mph)													
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
600/65 R38	DW20 B W18L	600 23.6	1745 68.7	798 31.4	5236 206.1	153D	0.8	2790	2880	2660	2550	2430	1.0	4130	3770
							12	6150	6340	5860	5620	5350	15	9100	8300
							1.0	3190	3280	3030	2910	2770	1.3	4710	4290
							15	7030	7220	6670	6410	6100	18	10370	9450
							1.3	3710	3830	3540	3390	3230	1.6	5490	5010
							19	8170	8440	7800	7470	7110	24	12090	11040
							1.6	4200	4330	4000	3830	3650	2.0	6210	5660
							23	9250	9540	8810	8440	8040	29	13680	12470

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
		Speed,km/h(mph)													
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Opera tion	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Opera tion	16	25	31	40	psi	6	9
540/65 R26	W16L W18L	540 21.3	1370 53.9	615 24.2	4046 159.3	141D	0.8	1960	2010	1860	1790	1700	1.0	2890	2640
							12	4320	4430	4100	3940	3740	15	6370	5810
							1.2	2510	2580	2390	2290	2180	1.5	3710	3380
							17	5530	5680	5260	5040	4800	22	8170	7440
							1.4	2710	2800	2580	2480	2360	1.8	4010	3660
							20	5970	6170	5680	5460	5200	26	8830	8060
							1.6	2960	3050	2820	2700	2575	2.0	4380	3990
							23	6520	6720	6210	5950	5670	29	9650	8790

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm				mm	mm	mm	bar	Field Oper ation	25	40	50	65

		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
320/65 R16	W10 W9 W11	319 12.6	822 32.4	370 14.6	2466 97.1	117D	0.8	780	810	740	710	680	1.0	1160	1050
							12	1720	1780	1630	1560	1500	15	2560	2310
							1.4	1080	1110	1030	990	940	1.8	1600	1460
							20	2380	2440	2270	2180	2070	25	3520	3220
							2.0	1330	1370	1270	1220	1160	2.5	1970	1800
							29	2930	3020	2800	2690	2560	36	4340	3960
							2.4	1480	1520	1410	1350	1285	3.0	2180	1990
							35	3260	3350	3110	2970	2830	44	4800	4380

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
320/65 R18	W10 W9 W11	319 12.6	873 34.4	395 15.6	2619 103.1	109D	0.8	780	810	740	710	680	1.0	1160	1050
							12	1720	1780	1630	1560	1500	15	2560	2310
							1.0	900	920	850	820	780	1.3	1330	1210
							15	1980	2030	1870	1810	1720	19	2930	2670
							1.4	1090	1130	1040	1000	950	1.8	1620	1470
							20	2400	2490	2290	2200	2090	26	3570	3240
							1.6	1180	1230	1130	1080	1030	2.0	1750	1600
							23	2600	2710	2490	2380	2270	29	3850	3520

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
340/65 R18	W11 W10 W12	343 13.5	899 35.4	406 16	2697 106.2	122D	0.8	910	940	870	830	790	1.0	1340	1220
							12	2000	2070	1920	1830	1740	15	2950	2690
							1.4	1270	1300	1200	1160	1100	1.8	1870	1710
							20	2800	2860	2640	2560	2420	25	4120	3770
							2.0	1550	1600	1480	1420	1350	2.5	2300	2090
							29	3410	3520	3260	3130	2970	36	5070	4600
							2.4	1730	1780	1640	1580	1500	3.0	2550	2330
							35	3810	3920	3610	3480	3300	44	5620	5130

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
340/65 R20	W11 W10 W12	343 13.5	950 37.4	431 17	2850 112.2	124D	0.8	840	870	800	770	730	1.0	1240	1130
							12	1850	1920	1760	1700	1610	15	2730	2490
							1.4	1180	1220	1130	1080	1030	1.8	1750	1600

							20	2600	2690	2490	2380	2270	25	3850	3520
							2.0	1660	1710	1580	1510	1440	2.5	2450	2230
							29	3660	3770	3480	3330	3170	36	5400	4910
							2.4	1840	1900	1750	1680	1600	3.0	2720	2480
							35	4050	4190	3850	3700	3520	44	5990	5460

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
420/65 R20	W13 W11 W12	418 16.5	1054 41.5	473 18.6	3113 122.6	135D	0.8	1320	1360	1260	1210	1150	1.0	1960	1780
							12	2910	3000	2780	2670	2530	15	4320	3920
							1.4	1830	1880	1740	1670	1590	1.8	2700	2460
							20	4030	4140	3830	3680	3500	25	5950	5420
							2.0	2250	2320	2150	2060	1960	2.5	3330	3040
							29	4960	5110	4740	4540	4320	36	7330	6700
							2.4	2510	2580	2390	2290	2180	3.0	3710	3380
							35	5530	5680	5260	5040	4800	44	8170	7440

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressur e	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Opera tion	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Opera tion	16	25	31	40	psi	6	9
420/65 R24	W13 W11 W12	418 16.5	1156 45.5	524 20.6	3414 134.4	138D	0.8	1290	1330	1230	1180	1120	1.0	1900	1740
							12	2840	2930	2710	2600	2470	15	4190	3830
							1.4	1840	1900	1750	1680	1600	1.8	2720	2480
							20	4050	4190	3850	3700	3520	26	5990	5460
							2.0	2060	2120	1960	1880	1790	2.5	3040	2770
							29	4540	4670	4320	4140	3940	36	6700	6100
							2.4	2290	2360	2180	2090	1990	3.0	3380	3080
							35	5040	5200	4800	4600	4380	44	7440	6780
							3.2	2710	2800	2580	2480	2360	4.0	4010	3660
							46	5970	6170	5680	5460	5200	58	8830	8060

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation				Cyclic Operation			
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
440/65 R20	W14L W13L W15L	441 17.4	1080 42.5	483 19	3240 127.6	138D	0.8	1290	1330	1230	1180	1120	1.0	1900	1740
							12	2840	2930	2710	2600	2470	15	4190	3830
							1.4	1840	1900	1750	1680	1600	1.8	2720	2480
							20	4050	4190	3850	3700	3520	26	5990	5460
							2.0	2440	2510	2330	2230	2120	2.5	3600	3290
							29	5370	5530	5130	4910	4670	36	7930	7250

		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
480/65 R24	W15L W14L	479 18.9	1234 48.6	561 22.1	3644 143.5	133D	0.8	1590	1640	1510	1450	1380	1.0	2350	2140
							12	3500	3610	3330	3190	3040	15	5180	4710
							1.0	1810	1860	1720	1650	1570	1.3	2670	2430
							15	3990	4100	3790	3630	3460	18	5880	5350
							1.4	2200	2260	2090	2010	1910	1.8	3250	2960
							20	4850	4980	4600	4430	4210	25	7160	6520
							1.6	2370	2440	2260	2160	2060	2.0	3500	3190
							23	5220	5370	4980	4760	4540	29	7710	7030

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)							
								Speed,km/h(mph)							
		SW	OD					Non-Cyclic Operation					Cyclic Operation		
		mm	mm	mm	mm	mm	bar	Field Operation	25	40	50	65	bar	10	15
		in	in	in	in	in	psi	Field Operation	16	25	31	40	psi	6	9
480/65 R24	W15L W14L	479 18.9	1234 48.6	561 22.1	3644 143.5	140D	0.8	1590	1640	1510	1450	1380	1.0	2350	2140
							12	3500	3610	3330	3190	3040	15	5180	4710
							1.2	2000	2060	1910	1830	1740	1.5	2960	2700
							17	4410	4540	4210	4030	3830	22	6520	5950
							2.0	2590	2670	2460	2360	2250	2.5	3830	3490
							29	5700	5880	5420	5200	4960	36	8440	7690
							2.4	2880	2960	2740	2630	2500	3.0	4250	3880
							35	6340	6520	6040	5790	5510	44	9360	8550