

HI-FLEX IMPLEMENT



Agriculture

Fronts & Implements

Radial



1 (IF Construction) Carry heavier load at low inflation pressure

2 (Rounded Shoulder) Less damage to soil and crops

3 (Steel belt at crown) Puncture resistance

4 (Reinforced sidewall & bead) Longer tire life

Sizes

Size	Rim
IF 240/80R15	8LB
IF 265/85R15	8LB
IF 280/70R15	W8
IF 320/70R15	W10

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)			
								Speed,km/h(mph)			
		SW	OD					Mixed Application			
		mm	mm				bar	10	20	30	40 - 65
		in	in	in	in	in	psi	6	12	19	25 - 40
IF 240/80R15	8LB	245 9.6	765 30.1	339 13.3	2271 89.4	125D	0.8	710	600	580	560
							12	1560	1320	1280	1230
							1.2	900	770	740	710
							17	1980	1700	1630	1560
							1.6	930	790	760	730
							23	2050	1740	1670	1610
							2.4	1460	1240	1200	1150
							35	3220	2730	2640	2530
							3.6	2100	1780	1720	1650
							52	4630	3920	3790	3630

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)			
								Speed,km/h(mph)			
		SW	OD					Mixed Application			
		mm	mm				bar	10	20	30	40 - 65
		in	in	in	in	in	psi	6	12	19	25 - 40
IF 265/85R15	8LB	270 10.6	831 32.7	364 14.3	2467 97.1	129D	0.8	880	750	720	690
							12	1940	1650	1590	1520
							1.2	1110	950	910	875
							17	2440	2090	2000	1930
							1.6	1380	1180	1130	1090
							23	3040	2600	2490	2400
							2.4	1840	1570	1510	1450
							35	4050	3460	3330	3190
							3.6	2350	2000	1920	1850
							52	5180	4410	4230	4070

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)			
								Speed,km/h(mph)			
		SW	OD					Mixed Application			
		mm	mm				bar	10	20	30	40 - 65
		in	in	in	in	in	psi	6	12	19	25 - 40
IF 280/70R15	W8	280 11	773 30.4	342 13.5	2295 90.4	137D	0.8	800	680	660	630
							12	1760	1500	1450	1390
							2.0	1500	1270	1230	1180
							29	3300	2800	2710	2600
							3.0	1970	1670	1610	1550
							44	4340	3680	3550	3410
							4.0	2480	2110	2030	1950
							58	5460	4650	4470	4300
							4.8	2920	2480	2390	2300
							70	6430	5460	5260	5070

Size	RIM	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended load,kg (lbs)			
								Speed,km/h(mph)			
		SW	OD					Mixed Application			
		mm	mm				bar	10	20	30	40 - 65
		in	in	in	in	in	psi	6	12	19	25 - 40
IF 320/70R15	W10	320 12.6	829 32.6	364 14.3	2461 96.9	146D	0.8	1140	970	940	900
							12	2510	2140	2070	1980
							2.0	2030	1730	1660	1600

							29	4470	3810	3660	3520
							3.0	2630	2240	2150	2070
							44	5790	4930	4740	4560
							4.0	3260	2780	2670	2570
							58	7180	6120	5880	5660
							5.2	3810	3240	3120	3000
							75	8390	7140	6870	6610