RPG

CEAT SPECIALTY

FLOTATION T422

FEATURE
- Tough nylon casing Strong brad buldle

BENEFIT
- High load carrying capacity

FEATURE
- Rounded shoulder

BENEFIT
- Reduced damage to crops

FEATURE
- Larger volume and footprint

BENEFIT
- Reduced compaction

MACHINERY



Trailer

Size	PR	Rim Width	Unloaded dimension		Static Circum-ference	Rolling Circum-ference	Infl. press.	Load Carrying Capacity					Tread Depth
			SW	OD				Load, Speed Symbol		Speed	Max Load (Free Rolling)	Max Load (Drive wheel)	
			mm	mm	mm	mm	Bar	Free Rolling	Drive Wheel	kmph	kg	kg	mm
		in	in	in	in	in	Psi			mph	lbs	lbs	in
600/55-22.5	12 PR	20.00 DC	600	1238	540	3715	**2**	**164 / 160**	**151 / 148**	**40**	**5000**	**3450**	**24**
							29	A8 / B	A8 / B	25	11023	7606	0.9
	16 PR		23.6	48.7	21.3	146.3	**2.6**	**169 / 166**	**156 / 153**	**40**	**5800**	**4000**	**24**
							38	A8 / B	A8 / B	25	12787	8818	0.9

All tires confirms ETRTO T&RA & STRO standards